



Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Electronic Spray Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning and care agent Impregnating substance.

1.3. Details of the supplier of the safety data sheet

Company name:	CTP-GmbH	
Street:	Saalfelder Strasse 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, DiplChem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	
1.4. Emergency telephone	For Germany: +49-361-730730 (24	hours/7 days)
<u>number:</u>		

Further Information

Article Number: 22092

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label propan-2-ol; isopropyl alcohol; isopropanol

Danger

Signal word:

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 2 of 8

Precautionary statements

oouullonaly olulonion	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Solvent mixture Auxiliary material

Aerosol propellent:

Propane/butane-mixture

Hazardous components

Chemical name		Quantity	
EC No	Index No	REACH No	
Classification according to Regula	ation (EC) No. 1272/2008 [CLP]	•	
butane			25 - < 30 %
203-448-7	601-004-00-0		
Flam. Gas 1; H220			
propane			
200-827-9	601-003-00-5		
Flam. Gas 1; H220			
propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
200-661-7		01-2119457558-25	
Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336		
	EC No Classification according to Regula butane 203-448-7 Flam. Gas 1; H220 propane 200-827-9 Flam. Gas 1; H220 propan-2-ol; isopropyl alcohol; iso 200-661-7	EC No Index No Classification according to Regulation (EC) No. 1272/2008 [CLP] butane 203-448-7 601-004-00-0 Flam. Gas 1; H220 propane 200-827-9 601-003-00-5 Flam. Gas 1; H220 propan-2-ol; isopropyl alcohol; isopropanol	EC No Index No REACH No Classification according to Regulation (EC) No. 1272/2008 [CLP] butane 203-448-7 601-004-00-0 Index No Flam. Gas 1; H220 Flam. Gas 1; H220 500-827-9 601-003-00-5 Index No Flam. Gas 1; H220 Flam. Gas 1; H220 500-827-9 601-003-00-5 Index No Flam. Gas 1; H220 Index No Flam. Gas 1; H220 Index No Index No

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 3 of 8

In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an opthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur: unconsciousness. Intoxication, vomiting, drowsiness, Headache.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Carbon dioxide (CO2). Water fog. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Explosive. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 4 of 8

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	transparent
Odour:	characteristic

Test method

Changes in the physical state	
Melting point:	ca 190 °C
Initial boiling point and boiling range:	ca 42 °C
Flash point:	< 0 °C
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	ca. 400 °C
9.2. Other information	
No data	





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 5 of 8

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No dangerous reactions are known. No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
106-97-8	butane					
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	oral	LD50	5280 mg/kg	Rat		
	dermal	LD50	12800 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50	47,5 mg/l	Rat		

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source	
67-63-0	propan-2-ol; isopropyl alcohol; i	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50	1000 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50	13299 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water.





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 6 of 8

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

160504

Do not dispose with household waste.

Waste disposal number of waste from residues/unused products

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances

Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances Classified as hazardous waste.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
	Propane/butane-mixture
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
	2
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Hazard No:	-





D: () () (0 (0 00))		
Print date: 16.12.2015	Product code: 407	Page 7 of 8
Tunnel restriction code:	D	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
	Propane/butane-mixture	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	E0	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
	Propane/butane-mixture	
14.3. Transport hazard class(es):	2.1	
<u>14.4. Packing group:</u> Hazard label:	- 2.1	
Marine pollutant:	-	
Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity:	1000 mL E0	
Excepted quantity: EmS:	EU F-D, S-U	
Air transport (ICAO)		
14.1. UN number:	UN 1950	
<u>14.2. UN proper shipping name:</u>	AEROSOLS	
	Propane/butane-mixture	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	EO	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	





Electronic Spray Aerosol

Print date: 16.12.2015

Product code: 407

Page 8 of 8

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Contains:

> 30 % aliphatic hydrocarbons

National regulatory information

Water contaminating class (D):

2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)