

**Teflon White Grease**

Print date: 17.12.2015

Product code: 1423

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Teflon White Grease

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**care agent  
Lubricants**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP-GmbH	
Street:	Saalfelder Strasse 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	

**1.4. Emergency telephone number:**

For Germany: +49-361-730730 (24 hours/7 days)

**Further Information**

Article Number: 22094

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazardous components which must be listed on the label**

Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light

**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 2 of 9

H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing aerosole.  
P271 Use only outdoors or in a well-ventilated area.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of this material and its container to hazardous or special waste collection point.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Surface tension compounds  
corrosion preventing agent  
Anti wear agents not classified

Aerosol propellant:  
Propane/butane-mixture

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light			50 - < 55 %
	265-151-9		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			20 - < 25 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
106-97-8	butane			20 - < 25 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Move victim to fresh air. Put victim at rest and keep warm.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

**Teflon White Grease**

Print date: 17.12.2015

Product code: 1423

Page 3 of 9

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

**After contact with eyes**

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

**After ingestion**

Let water be drunken in little sips (dilution effect). Consult physician.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. - No smoking.

Do not breathe gas/fumes/vapour/spray.

**6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Wipe up with absorbent material (eg. cloth, fleece).

**6.4. Reference to other sections**

No data

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 4 of 9

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Closed devices: Vapours / aerosols must be extracted by suction immediately at point of origin.  
Avoid contact with skin and eyes.

##### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Storage in compliance with official storage regulations of aerosols.  
Do not store at temperatures over: 50 °C

##### Further information on storage conditions

Packaging materials: metal.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

##### Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

##### Hand protection

Tested protective gloves are to be worn:  
NBR (Nitrile rubber). : Material thickness: 0.4 – 0.5 mm , penetration time >= 240 min  
FKM (Fluoroelastomer (Viton)). : Material thickness: 0.4 – 0.5 mm, penetration time >= 240 min

##### Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

##### Respiratory protection

Provide for good ventilation, when develop aerosols/mist. In case of insufficient ventilation, wear suitable respiratory equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
Colour: white  
Odour: characteristic

Test method

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 5 of 9

### Changes in the physical state

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	
Ignition temperature:	> 250 °C
Density (at 20 °C):	0,70 g/cm³
Water solubility: (at 20 °C)	insoluble

### Solubility in other solvents

Organic solvents

### 9.2. Other information

No data

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No decomposition when used as intended.

### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

Do not store at temperatures over: 50 °C

Keep away from heat.

### 10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light				
	oral	LD50	>2000 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	>20 mg/l		
	inhalative (4 h) aerosol	LC50	>5 mg/l	Rat	
106-97-8	butane				
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS

#### Irritation and corrosivity

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 6 of 9

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.  
Irritation of eyes: Irritant effect possible.  
After ingestion:  
Harmful: may cause lung damage if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light					
	Acute crustacea toxicity	EC50	1-10 mg/l	48 h	Daphnia magna	
	Crustacea toxicity	NOEC	1 mg/l		Daphnia magna	

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

Swims on the water.  
Low potential of bio-accumulation.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

No information available.

### 12.6. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Do not dispose with household waste.  
Do not empty into drains or the aquatic environment.  
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.  
Arrange about the exact waste code with the local waste disposal expert.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423


Page 7 of 9

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

### SECTION 14: Transport information

#### Land transport (ADR/RID)


**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Hazard No: -  
 Tunnel restriction code: D

#### Inland waterways transport (ADN)


**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

#### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: -  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0

## Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 8 of 9

EmS: F-D, S-U

### Air transport (ICAO)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light

### 14.6. Special precautions for user

No information available.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

#### Additional information

Contains:  
 > 30 % aliphatic hydrocarbons

#### National regulatory information

Water contaminating class (D): 2 - water contaminating

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H225 Highly flammable liquid and vapour.  
 H229 Pressurised container: May burst if heated.





## Safety Data Sheet

**bluechem**   
**GROUP**

according to Regulation (EC) No 1907/2006

### Teflon White Grease

Print date: 17.12.2015

Product code: 1423

Page 9 of 9

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*