

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Triple X Air Intake System Cleaner -Diesel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Company name:	CTP-GmbH	
Street:	Saalfelder Strasse 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	

1.4. Emergency telephone

For Germany: +49-361-730730 (24 hours/7 days)

number:

Further Information

Article Number: 33381

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

mixture of hydrocarbons (aromatic) C9-C10

Distillates (petroleum, gasoline), hydrotreated light

Signal word: Danger

Pictograms:



Hazard statements

H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 2 of 9

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of this material and its container to hazardous or special waste collection point.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Solvent mixture
Synthetic agent combinations
Lubricants
Cleaning and care agent

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
N/A	mixture of hydrocarbons (aromatic) C9-C10			50 - < 55 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
108-32-7	Propylene carbonate			20 - < 25 %
	203-572-1			
	Eye Irrit. 2; H319			
100-51-6	Benzyl alcohol			20 - < 25 %
	202-859-9		01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H302 H332 H319			
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light			10 - < 15 %
	919-164-8		01-2119473977-17	
	STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H372 H304 H412 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 3 of 9

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 4 of 9

6.3. Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).
Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.
Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Packaging materials: metal.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Protective and hygiene measures**

When using do not eat, drink or smoke.
Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	aromatic

Test method**Changes in the physical state**

Initial boiling point and boiling range:	110 - 120 °C
Flash point:	> 65 °C



Safety Data Sheet

bluechem 
GROUP

according to Regulation (EC) No 1907/2006

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 5 of 9

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

> 200 °C

Density (at 20 °C):

0.92-0.96 g/cm³

Water solubility:
(at 20 °C)

insoluble

Solubility in other solvents

Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents.

acid, concentrated.

Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 6 of 9

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
N/A	mixture of hydrocarbons (aromatic) C9-C10				
	oral	LD50	>3000 mg/kg	Rat	
	dermal	LD50	>3160 mg/kg	Rat	
108-32-7	Propylene carbonate				
	oral	LD50	29000 mg/kg	Rat	
	dermal	LD50	>20000 mg/kg	Rabbit	
100-51-6	Benzyl alcohol				
	oral	LD50	1230 mg/kg	Rat	
	dermal	LD50	2000 mg/kg	Rabbit	
	inhalative vapour	ATE	11 mg/l		
	inhalative (4 h) aerosol	LC50	>4,178 mg/l	Rat	
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>3400 mg/kg	Rabbit	

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
108-32-7	Propylene carbonate					
	Acute fish toxicity	LC50	5300 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50	900 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50	500 mg/l	48 h	Daphnia magna	
100-51-6	Benzyl alcohol					
	Acute fish toxicity	LC50	460 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	640 mg/l	96 h	Scenedesmus quadricauda	
	Acute crustacea toxicity	EC50	400 mg/l	48 h	Daphnia magna (Big water flea)	
64742-82-1	Distillates (petroleum, gasoline), hydrotreated light					
	Acute fish toxicity	LC50	10-100 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	50-100 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	10-22 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

No information available.

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 7 of 9

12.3. Bioaccumulative potential

Swims on the water.
Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.
Do not allow to enter into surface water or drains.
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.
Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.
Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M6
Special Provisions: 274 335 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389


Page 8 of 9



Classification code: M6
Special Provisions: 274 335 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)


14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Marine pollutant: P
Special Provisions: 274, 335
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: A97 A158
Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: mixture of hydrocarbons (aromatic) C9-C10

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information available.

Triple X Air Intake System Cleaner -Diesel

Print date: 15.12.2015

Product code: 1389

Page 9 of 9

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

Contains:

5 - 15 % hydrocarbons, aliphatic.

> 30 % hydrocarbons, aromatic.

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)