

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Autoprofi DPF and Catalyst Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

cleaning solvent for diesel particulate filter

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

For Germany: +49-361-730730 (24 hours/7 days)

Further Information

Article Number: 43159

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye damage.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2-aminoethanol, ethanolamine

Signal word: Danger

Pictograms:



Hazard statements

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 2 of 8

	smoking.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Special labelling of certain mixtures

18,0 % by mass of the contents are flammable.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aerosols, non-flammable

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
34590-94-8	(2-methoxymethylethoxy)propanol			10 -< 25 %
	252-104-2		01-2119450011-60	
141-43-5	2-aminoethanol, ethanolamine			3 -< 5 %
	205-483-3	603-030-00-8		
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B; H332 H312 H302 H314			
7320-34-5	tetra-potassium-diphosphate (potassium-pyro-phosphate)			1,0 -< 2,5 %
	230-785-7			
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 3 of 8

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur:

unconsciousness. Intoxication. vomiting. drowsiness. Headache.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.

Carbon dioxide (CO₂).

Water fog.

alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes.

Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C

Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 4 of 8

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
34590-94-8	(2-methoxymethylethoxy) propanol	50	308		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL

8.2. Exposure controls

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	aerosole
Colour:	transparent
Odour:	characteristic

Test method

pH-Value (at 20 °C):	11,4
----------------------	------

Changes in the physical state

Initial boiling point and boiling range:	100 °C
--	--------

Flash point:	75 °C
--------------	-------

Lower explosion limits:	1,1 vol. %
-------------------------	------------

Upper explosion limits:	14,0 vol. %
-------------------------	-------------

Ignition temperature:	270 °C
-----------------------	--------

Vapour pressure: (at 20 °C)	8000 hPa
--------------------------------	----------

Density (at 20 °C):	1,011 g/cm ³
---------------------	-------------------------

Solvent content:	Organic solvents: 18 % Water.: 80 %
------------------	--

9.2. Other information

Solid content:	1,0 %
----------------	-------

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 5 of 8

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
141-43-5	2-aminoethanol, ethanolamine				
	oral	LD50	1515 mg/kg	Rat	
	dermal	LD50	1025 mg/kg	Rabbit	IUCLID
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
141-43-5	2-aminoethanol, ethanolamine					
	Acute fish toxicity	LC50	150 mg/l	96 h	Onchorhynchus mykiss	IUCLID
	Acute algae toxicity	ErC50	22 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	65 mg/l	48 h	Daphnia magna	
7320-34-5	tetra-potassium-diphosphate (potassium-pyro-phosphate)					
	Acute fish toxicity	LC50	>750 mg/l	96 h	Leuciscus idus	

12.2. Persistence and degradability

No information available.

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 6 of 8

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-43-5	2-aminoethanol, ethanolamine	-1,91 (25°C)

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.2



Classification code: 5A
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 3
 Hazard No: -
 Tunnel restriction code: E

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 7 of 8

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.2



Classification code: 5A
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.2
14.4. Packing group: -
 Hazard label: 2.2



Marine pollutant: -
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.2
14.4. Packing group: -
 Hazard label: 2.2



Special Provisions: A98 A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

according to Regulation (EC) No 1907/2006

Autoprofi DPF and Catalyst Cleaner

Print date: 27.01.2016

Product code: 1669

Page 8 of 8

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 951,8 g/l

Additional information

Contains:

< 5 % Phosphate

< 5 % nonionic tensides

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)