



Safety Data Sheet

bluechem 
GROUP

according to Regulation (EC) No 1907/2006

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Petrol System Cleaner LPG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Fuel Systems

1.3. Details of the supplier of the safety data sheet

Company name:	CTP-GmbH	
Street:	Saalfelder Strasse 35	
Place:	D-07338 Leutenberg	
Telephone:	+4936734/230-0	Telefax: +4936734/230-22
e-mail:	hotline@ctp-gmbh.de	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +4936734/230-19
Internet:	www.ctp-gmbh.de	

1.4. Emergency telephone number:

For Germany: +49-361-730730 (24 hours/7 days)

Further Information

Article Number: 33343, 33345, 33346

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Carcinogenicity: Carc. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

May cause drowsiness or dizziness.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

xylene

propan-2-ol; isopropyl alcohol; isopropanol

Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

Hydrocarbons, C10, aromatics, >1% naphthalene

Signal word: Danger

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 2 of 11

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Surface tension compounds
Detergents, Dispersants
Synthetic agent combinations
Anti wear agents not classified

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1330-20-7	xylene			30 - < 35 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
67-64-1	acetone; propan-2-one; propanone			20 - < 25 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			10 - < 15 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates			5 - < 10 %
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066			
37205-87-1	isononylphenole, ethoxylised			1 - < 5 %
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 2; H302 H318 H411			
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene			1 - < 5 %
	919-284-0		01-2119463588-24	
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411			
64742-94-5	Hydrocarbons, C10-C13, aromatics, >1% naphthalene			< 1 %
	926-273-4		01-2119451151-53	
	Carc. 2, Asp. Tox. 1, Aquatic Chronic 2; H351 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 4 of 11

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 5 of 11

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Packaging materials: metal.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: light red
 Odour: aromatic

Test method

Changes in the physical state

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 6 of 11

Initial boiling point and boiling range:	110 - 116 °C
Flash point:	-7,5 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	> 200 °C
Vapour pressure: (at 20 °C)	20 hPa
Density (at 20 °C):	0.78-0.82 g/cm ³
Water solubility: (at 20 °C)	insoluble

Solubility in other solvents

Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalies (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO₂).**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 7 of 11

Acute toxicity

CAS No	Chemical name			
	Exposure routes	Method	Dose	Species
1330-20-7	xylene			
	oral	LD50	4300 mg/kg	Rat
	dermal	LD50	3200 mg/kg	Rabbit
	inhalative (4 h) vapour	LC50	21,7 mg/l	Rat
	inhalative aerosol	ATE	1,5 mg/l	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	oral	LD50	5280 mg/kg	Rat
	dermal	LD50	12800 mg/kg	Rabbit
	inhalative (4 h) vapour	LC50	47,5 mg/l	Rat
67-64-1	acetone; propan-2-one; propanone			
	oral	LD50	5800 mg/kg	Rat
	dermal	LD50	20000 mg/kg	Rabbit
	inhalative (4 h) vapour	LC50	76 mg/l	Rat
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			
	oral	LD50	>5000 mg/kg	Rat
	dermal	LD50	>5000 mg/kg	Rabbit
	inhalative (4 h) aerosol	LC50	>5 mg/l	Rat
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates			
	oral	LD50	>5000 mg/kg	Rat
	dermal	LD50	>5000 mg/kg	Rabbit
	inhalative (4 h) aerosol	LC50	>5 mg/l	Rat
37205-87-1	isononylphenole, ethoxylised			
	oral	LD50	2000 mg/kg	Rat

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 8 of 11

CAS No	Chemical name				
	Aquatic toxicity	Method	Dose	[h] [d]	Species
1330-20-7	xylene				
	Acute fish toxicity	LC50	26,7 mg/l	96 h	Pimephales promelas
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas
	Acute algae toxicity	ErC50	1000 mg/l	72 h	Algae
	Acute crustacea toxicity	EC50	13299 mg/l	48 h	Daphnia magna
67-64-1	acetone; propan-2-one; propanone				
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata
	Acute crustacea toxicity	EC50	1000 mg/l	48 h	Daphnia magna
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata
	Acute crustacea toxicity	EC50	1000 mg/l	48 h	Daphnia magna
37205-87-1	isononylphenole, ethoxylised				
	Acute fish toxicity	LC50	1-10 mg/l	96 h	Brachydanio rerio
	Acute algae toxicity	ErC50	1-10 mg/l	72 h	Scenedesmus subspicatus
64742-94-5	Hydrocarbons, C10, aromatics, >1% naphthalene				
	Acute fish toxicity	LC50	2-5 mg/l	96 h	Fish
	Acute algae toxicity	ErC50	1-3 mg/l	72 h	Algae
	Acute crustacea toxicity	EC50	3-10 mg/l	48 h	Daphnia magna

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water. Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 9 of 11

Advice on disposal

Do not dispose with household waste.
Do not empty into drains or the aquatic environment.
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.
Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.
Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 10 of 11



Marine pollutant: -
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Contains:
15 - 30 % aliphatic hydrocarbons
> 30 % hydrocarbons, aromatic.
< 5 % phenole, ethoxylised

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Petrol System Cleaner LPG

Print date: 15.12.2015

Product code: 1412

Page 11 of 11

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)