

Automatic Transmission Conditioner

Product properties

Reduces friction, facilitates the switching operation and supports the preservation of gaskets and seals. This results in smoother shifting of gears and in a prolonged life span. The redeposition of resins and similar soilings is delayed.

Advantages:

- Increases the life span of the automatic transmission - the oxidation is slowed
- Reduces friction, operating and maintenance costs
- Optimum lubrication is guaranteed
- Improved power output
- Reduces heat loss
- Extends the oil change intervals

Our product is suitable for all automatic transmissions and automatic transmission fluids.

Area of application

For all torque converter, CVT and DSG transmissions except wet clutch.

Application

Add the Automatic Transmission Conditioner to the automatic transmission fluid and drain it together with the old one.

Consumption

150 ml for 1 ltr. oil

Reaction time

Works during operation

Technical data

Physical state: viscous

Colour: red

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.87 - 0.92 g/cm³

Water resistant

Available size	Item no.	PU
250ml	43236	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

02.12.2016