

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Ceramic Grease

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Lubricants

**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

**1.4. Emergency telephone number:**

For Germany: +49-361-730730 (24 hours/7 days)

**Further Information**

Article Number: 9742

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

**Regulation (EC) No. 1272/2008**

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 2 of 8

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of this material and its container to hazardous or special waste collection point.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Lubricant and additive.

Aerosol propellant:

Propane/butane-mixture

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1314-13-2	zinc oxide			15 - < 20 %
	215-222-5	030-013-00-7		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
106-97-8	butane			5 - < 10 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
N/A	Calcium-alkyl-naphthalen-sulfonate			1 - < 5 %
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove affected person from the danger area and lay down.

Change contaminated clothing.

**After inhalation**

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, seek medical treatment.

**After contact with eyes**

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Consult physician.

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 3 of 8

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

The following symptoms may occur:  
unconsciousness. Intoxication. vomiting. drowsiness. Headache.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Extinguishing powder.  
Carbon dioxide (CO<sub>2</sub>).  
Water fog.  
alcohol resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Concentrated vapors are heavier than air. Vapours may form explosive mixtures with air.  
Heating causes the generation of toxic gases.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes.  
Do not breathe gas/fumes/vapour/spray.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).  
Provide adequate ventilation.

**6.4. Reference to other sections**

Explosive. Vapours may form explosive mixtures with air.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

**Advice on protection against fire and explosion**

Vapours may form explosive mixtures with air.  
Keep away from sources of ignition. - No smoking.  
Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities**

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 4 of 8

**Requirements for storage rooms and vessels**

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C  
Heating causes rise in pressure with risk of bursting.

**Further information on storage conditions**

Keep away from heat.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
106-97-8	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Butane	1000	-	-	TWA (8 h)	
		-	-	-	STEL (15 min)	
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C4), Propane	1000	-	-	TWA (8 h)	
		-	-	-	STEL (15 min)	
1314-13-2	Zinc oxide, fume (Respirable Fraction)	-	2	-	TWA (8 h)	
		-	10	-	STEL (15 min)	

**8.2. Exposure controls**

**Protective and hygiene measures**

Keep away from food, drink and animal feedingstuffs.  
Remove contaminated, saturated clothing immediately.  
Wash hands before breaks and after work.  
Do not breathe gas/fumes/vapour/spray.  
Avoid contact with skin and eyes.

**Eye/face protection**

Wear tightly sealed safety glasses against possible splashes into the eyes.

**Hand protection**

Tested protective gloves are to be worn:

Butyl rubber.:  
penetration time: > 120 min  
Material thickness: >= 0,45 mm

**Respiratory protection**

Have to care for a good Ventilation at workplace.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
Colour: beige  
Odour: characteristic

**Test method**

**Changes in the physical state**

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 5 of 8

Flash point: > 250 °C  
Sustaining combustion: No data available  
Water solubility: not miscible  
(at 20 °C)

**9.2. Other information**

No data

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No decomposition when used as intended.

**10.3. Possibility of hazardous reactions**

No dangerous reactions are known.

**10.4. Conditions to avoid**

Do not store at temperatures over: 50 °C  
Keep away from heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No hazardous decomposition products are known.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
1314-13-2	zinc oxide			
	oral	LD50 > 5000 mg/kg	Rat	IUCLID
106-97-8	butane			
	inhalative (4 h) gas	LC50 273000 ppm	Rat	GESTIS
N/A	Calcium-alkyl-naphthalen-sulfonate			
	oral	LD50 > 2000 mg/kg	Rat	
	dermal	LD50 > 20000 mg/kg	Rabbit	

**Irritation and corrosivity**

Frequently or prolonged contact with skin may cause dermal irritation.  
Irritation of eyes: Irritant effect possible.

**Sensitising effects**

no danger of sensitization.

**SECTION 12: Ecological information**

**12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 6 of 8

No information available.

**12.3. Bioaccumulative potential**

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

No information available.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Do not dispose with household waste.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:**

UN 1950

**14.2. UN proper shipping name:**

AEROSOLS  
Propane/butane-mixture

**14.3. Transport hazard class(es):**

2

**14.4. Packing group:**

-

Hazard label:

2.1



**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 7 of 8

Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Hazard No: -  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Marine pollutant: P  
Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G

**Ceramic Grease**

Revision date: 08.05.2015

Product code: 1106

Page 8 of 8

Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: zinc oxide

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane

**Additional information**

Contains::

5 - 15 % anionic surfactants

**National regulatory information**

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*