

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Brake Cleaner, Acetone content

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

For Germany: +49-361-730730 (24 hours/7 days)

Further Information

Article Number: 32020, 32024, 32021, 32025

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light propan-2-ol; isopropyl alcohol; isopropanol
acetone; propan-2-one; propanone**Signal word:** Danger**Pictograms:**

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 2 of 10

Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing Vapour/aerosole.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water.
P312	Call a POISON CENTER/doctor if you feel unwell.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Petroleum (Gasoline)
Alcohol.
ketone.

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light			70 - < 75 %
	265-151-9		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			15 - < 20 %
	200-661-7		01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
67-64-1	acetone; propan-2-one; propanone			10 - < 15 %
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether			1 - < 5 %
	203-905-0		01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H312 H332 H315 H319			

Full text of H and EUH statements: see section 16.

Further Information

CAS-Nr. 64742-49-0: benzene < 0,1 % (Nota P)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 4 of 10

Suitable extinguishing mediaExtinguishing powder. Sand. alcohol resistant foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).

Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Packaging materials: metal.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 5 of 10

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
111-76-2	2-Butoxyethanol	20	98		TWA (8 h)	
		50	246		STEL (15 min)	
67-64-1	Acetone	500	1210		TWA (8 h)	
		-	-		STEL (15 min)	
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	BAA	200 mg/g	Creatinine	End of shift
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

8.2. Exposure controls

Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

Provide for good ventilation, when develop aerosols/mist. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: colourless
 Odour: aromatic

Test method

Changes in the physical state

Initial boiling point and boiling range: 60 - 100 °C

Flash point: < 0 °C

Lower explosion limits:

Upper explosion limits:

Density (at 20 °C): 0.6-0.7 g/cm³

Water solubility: insoluble
 (at 20 °C)

Solubility in other solvents

Organic solvents

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 6 of 10

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO)., Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light			
	oral	LD50 >2000 mg/kg	Rat	
	dermal	LD50 >2000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 >20 mg/l		
	inhalative (4 h) aerosol	LC50 >5 mg/l	Rat	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	oral	LD50 5280 mg/kg	Rat	
	dermal	LD50 12800 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 47,5 mg/l	Rat	
67-64-1	acetone; propan-2-one; propanone			
	oral	LD50 5800 mg/kg	Rat	RTECS
	dermal	LD50 20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50 76 mg/l	Rat	
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether			
	oral	ATE 500 mg/kg		
	dermal	ATE 1100 mg/kg		
	inhalative vapour	ATE 11 mg/l		
	inhalative aerosol	ATE 1,5 mg/l		

Irritation and corrosivity

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 7 of 10

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
64742-49-0	Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light				
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna	
	Crustacea toxicity	NOEC 1 mg/l		Daphnia magna	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50 13299 mg/l	48 h	Daphnia magna	
67-64-1	acetone; propan-2-one; propanone				
	Acute fish toxicity	LC50 5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 6100 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 8 of 10

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: P
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 9 of 10

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline), hydrotreated light

Additional information

Contains:

> 30 % hydrocarbons, aliphatic.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

- | | |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |



Safety Data Sheet

bluechem 
GROUP

according to Regulation (EC) No 1907/2006

Brake Cleaner, Acetone content

Revision date: 27.11.2015

Product code: 126

Page 10 of 10

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)