

Diesel Anti Gel 1:200

Product properties

High Performance Diesel System Care for diesel-flow improvement. Winter safe up to -33 °C.

- prevents thickening of the diesel fuel in extreme coldness
- prevents blocking of the fuel filter and fuel lines
- ensures a better cold start behaviour and smooth warmup running
- ensures optimised lubrication of all movable parts in diesel engines

Area of application

For all diesel engines.

Application

Product should be applied to the diesel system at temperatures above 0 °C prior to filling up the fuel tank. Make sure to add the product before gelling of the diesel fuel.

Consumption

250 ml for 60 ltr. fuel.

Reaction time

While engine is running

Technical data

Physical state: liquid

Colour: clear/colourless

Odour: characteristic

Flashpoint: 63 °C

not Explosive

Density at 68 °F: 0,82 - 0,83 g/cm³

Available size	Item no.	PU
250ml	43217	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

13.03.2017