

Water Remover

Product properties

Binds and reliably removes condensed water and moisture from the entire fuel system. Protects against rust and corrosion and increases the lifespan of the engine. Ensures a clean and powerful combustion, improves engine running and cold starting performance and optimises exhaust emission. Prevents ice formation.

Area of application

For all petrol and diesel powered engines.

Application

Add every 3-4 months to the fuel system before filling up.

Consumption

250 ml for 60 ltr. fuel

Reaction time

Works during operation

Technical data

Physical state: liquid

Colour: violet

Odour: aromatic

Initial boiling point and boiling range: 145 - 200 °C

Flashpoint: 35 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 6,5 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 4 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available size	Item no.	PU
250ml	43219	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

14.03.2017