

Injection System Clean

Product properties

Removes crust and coking from injection systems, cleans inlet valves and injection nozzles. Prevents rough running of the engine, power loss and start problems. Fuel consumption and exhaust gas emission will be reduced.

Area of application

For all petrol engines.

Application

Add to the fuel tank every 3 to 4 months before filling in the fuel.

Consumption

250 ml for 60 ltr. petrol

Reaction time

Works during operation

Technical data

Physical state: liquid

Colour: blue

Odour: aromatic

Initial boiling point and boiling range: 110 - 116 °C

Flashpoint: -5 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 12 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available size	Item no.	PU
250ml	43213	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

14.03.2017