

## Engine Oil Stop Leak

### Product properties

The combination of highly efficient and innovative components regenerates plastic and rubber seals in the oil circuit and keeps it soft. The oil loss through seals or piston rings is reduced or stopped, which reduces the oil consumption. In addition, abrasion and wear will be considerably reduced, the viscosity of the oil is kept stable and works against the oxidation of the engine oil. The usable lifetime of the engine will be extended.

### Area of application

For use in all 4-stroke- and diesel engines, transmissions, differentials, etc. This product is compatible with all commercially available oils.

### Application

Add to oil system. We recommend an oil system cleaning with Oil System Cleaner before using this product. Total Oil capacity according to manufacturer specifications must be observed.

### Consumption

250 ml sufficient for 5 liters of oil. Mixing ratio: 1:20

### Reaction time

while engine is running

### Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm<sup>3</sup>

Water resistant

Available size	Item no.	PU
250ml	43223	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

16.03.2017