

## Radiator Stop Leak

### Product properties

Radiator Stop Leak seals leaking radiators, heat converters, water pumps and flexible hoses. Radiator Stop Leak is compatible with all antifreeze brands.

### Area of application

For use in all water-cooled engines.

### Application

Shake well before use. Add the product to the coolant. Start the engine and open the heating valve and run engine for 5-10 minutes. After successful sealing process please check the coolant level.

### Consumption

250 ml sufficient to treat cooling systems of 4 - 8 litres capacity.

### Reaction time

Works during operation

### Technical data

Physical state: Jelly

Colour: green

Odour: noticeable

pH-Value (at 68 °F): 7

Initial boiling point and boiling range: 85 - 110 °C

Density at 68 °F: 0,95 - 1,1 g/cm<sup>3</sup>

Water soluble

Available size	Item no.	PU
250ml	43226	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

16.03.2017