

## Radiator Flush

### Product properties

Radiator Flush removes operational deposits in the entire cooling system. It removes also lime and fur deposits, protects against rust and corrosion, dissolves dangerous radiator sludge and cleans water coolers, boilers and heat exchangers. The product makes valves, thermostats and water pumps free again. The use of Radiator Flush increase the reliability and lifetime of the engine. Also the heating and cooling performance will be improved.

### Area of application

For use in all cooling water circuits of petrol and diesel engines or industrial equipment

### Application

Add the product to the coolant. Start the engine and open the heating valve, run engine for 10-15 min. Drain system completely and flush with fresh water. Refill the system with coolant in line with manufacturer's instructions. We further recommend adding of Radiator Conditioner.

### Consumption

250 ml sufficient to treat cooling systems of 8 litres capacity.

### Reaction time

15-40 minutes, depending on the size of the system

### Technical data

Physical state: liquid

Colour: yellow

Odour: odourless

pH-Value (at 68 °F): 0-1

Melting point: < 0 °C

Initial boiling point and boiling range: > 100 °C

Density at 68 °F: 1,07 g/cm<sup>3</sup>

Water soluble

Available size	Item no.	PU
250ml	43227	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

16.03.2017