

Automatic Transmission Flush

Product properties

Reliably dissolves and removes contamination, oxidised oil residues and other deposits from the entire gear oil system. The whole system is thoroughly cleaned.

- Complete removal of contaminants
- Reduces unpleasant noises and ensures a safe and smooth operation of the transmission
- Optimizes the switching behavior
- Avoid costly repairs

WHY USE?

Today's gear oils are usually of good quality but they can not prevent, that operationally caused contaminations and oxidized oil residues deposited with time on the transmission parts. Result: performance degradation and switching problems. The system runs rough and dirty parts are loaded higher. Our Automatic Transmission Flush will help. The product is suitable for all automatic transmission oils.

Area of application

In all kinds of automatic transmissions

Application

Add the product to the oil system before exchanging the gear oil. Run the system for approx. 10-15 minutes under frequent load alteration. Afterwards carry out the exchange of the gear oil in accordance to the manufacturer's instructions.

Consumption

250 ml for cars / approx. 5% of the transmission oil volume for trucks

Reaction time

approx. 10-15 minutes

Technical data

Physical state: liquid

Colour: yellow

Odour: aromatic

Initial boiling point and boiling range: 180 - 220 °C

Flashpoint: 63 °C

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.82 - 0.90 g/cm³

Water resistant

Available size	Item no.	PU
250ml	43235	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

20.03.2017