

# Radiator Oil Cleaner 2-C

## Product properties

Reliably cleans the entire cooling system and durably removes oily deposits and sludge caused by defect cylinder head gaskets or leaking radiators.

## Area of application

Cooling system cleaning for all closed water-cooled systems. Also suitable for heat exchangers. Mixable with all kinds of coolants.

## Application

Add the product to the cooling system before exchanging the coolant. Open the heating valve. Let the engine run for approx. 15 minutes at midrange speed and drain the fluid afterwards. Please remove all expansion tanks which are not part of the coolant circle and clean them manually. Afterwards rinse the entire cooling system thoroughly with clear water. Finally please carry out the exchange of the coolant in accordance to the manufacturer's instructions.

## Consumption

300 ml sufficient to treat cooling systems of 5 to 10 litres capacity. For lower or higher filling quantities, decrease or increase the product's application amount by 50 ml per 1 litre coolant.

## Reaction time

approx. 15 minutes

## Technical data

Physical state: liquid

Colour: red

Odour: aromatic

Initial boiling point and boiling range: 110 - 116 °C

Flashpoint: -6.5 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 12 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available size	Item no.	PU
300ml	43230	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

20.03.2017