

Easy Gear

Product properties

The highly effective anti-friction barrier seals all the internal surfaces of engines and equipment. Remarkably reduces wear and tear and guarantees optimized lubrication throughout the temperature range. Keeps seals, shaft seals and "o" rings soft and supple. Easy Gear ensures smooth gear changing and quieter operation. Improves the temperature bandwidth and helps to prevent oxidation of the gear oil.

Area of application

Suitable for all manual gearboxes and differentials. Do not use for automatic transmissions or wet clutches.

Application

Add to the transmission oil system. This product is compatible with all commercially available gear oils.

Consumption

50 ml sufficient to treat 2 - 3 litres of Transmission oil.

Reaction time

Works during operation

Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm³

Water resistant

| Available size | Item no. | PU |
|----------------|----------|----|
| 50ml | 43238 | 24 |



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

20.03.2017