

Electronic Spray

Product properties

Electronic Sprays excellent creep characteristic ensures displacement of moisture from electrical cables, connectors and contacts. Forms a micro-thin film and protects electrical connectors against moisture. Cleans contacts, removes contaminations and dissolves encrusted layers. Acts as a preserver and prevents electrical creep. Reduces voltage drop. Ensures electrical connections are functionally secure. Reduces wear and disperses moisture. Does not harm paintwork, plastic or rubber parts.

Area of application

For maintenance and care of electrical equipment and components, such as push or snap connectors, lamps, fuses, distributor caps, circuit breakers, switches, battery terminals, alternators, starter motors etc. Also suitable for the lubrication of precision engineered parts such as door mechanisms, car-jacks, slide-ways and Bowden cables.

Application

Spray the product evenly onto the parts being treated from a distance of approx. 30 cm and allow it to penetrate. If necessary, remove dissolved contaminants and treat the surface again.

Consumption

Approx. 5-10 depending on the application

Reaction time

approx. 60 seconds

Technical data

Physical state: aerosol

Colour: clear/colourless

Odour: characteristic

Boiling point (ERBP): ca. - 190 °C

Boiling point (ERBP): ca. - 42 °C

Flashpoint: < 0 °C

Lower explosion limit: 1,5 Vol.-%

Upper explosion limit: 9,4 Vol.-%

Ignition temperature: ca. 400 °C

Available size	Item no.	PU
400ml	43198	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

21.03.2017