Nano Engine Protect

Product properties

Nano Engine Protect creates a highly active nano barrier in the oil which protects all the internal surfaces of engines and equipment such as oil system, manual gearboxes and differentials. Seals, o-rings and shaft seals are kept supple. Improved oil flow during cold start, smoother and quieter engine running, improved performance, extended life of equipment, and excellent "run dry" emergency properties

Area of application

Service product for use in the oil system of 4-stroke petrol and diesel engines. Applicable for common rail as well as pump injector fuel systems and recommended for engines with turbo charger, catalytic converter and DPF filters. Compatible with all engine oils.

Application

Add to oil system after each oil change. We recommend cleaning the oil system with Engine Clean before use. Observe the maximum oil quantity! In power-steering systems, manual transmissions und differentials use at ratio 1:10.

Note: When using in vehicles with wet clutch, observe the manufacturer's instructions!

Consumption

250 ml sufficient for 5 liters of oil. Mixing ratio: 1:20

Reaction time

while engine is running

Technical data

Physical state: viscous

Colour: brown Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.90 - 0.95 g/cm3

Water resistant

Viscosity / kinematic (at 104 °F): 17,2 mm²/s

Available size Item no. PU 250ml 43218 24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

