

Radiator Stop Leak (RSL)

Radiator Stop Leak

Product properties

PRO-TEC Radiator Stop Leak reliable seals leaky water coolers and heat exchangers, leaking water pumps and valves, loose connections and cracked coolant hoses without clogging the system. The use of PRO-TEC Radiator Stop Leak increase the reliability and lifetime of the engine. Finally, the environmental impact is reduced through dense cooler. PRO-TEC Radiator Stop Leak is also ideally suitable for preventive applications.

Area of application

Usage in all units and systems with closed water cooling circuit

Application

Admit PRO-TEC Radiator Stop Leak to the coolant and set the heater to heat. After that check the sealing coolant level. Contains no toxic or irritant substances.

Consumption

375 ml sufficient for 5 - 10 liters of cooling water. Mix Ratio 1:20

Reaction time

While engine is running

Technical data

Physical state: liquid

Colour: green

Odour: noticeable

Initial boiling point and boiling range: 85 - 110 °C

Density at 68 °F: 0,95 - 1,1 g/cm³

Water soluble

Available size	Item no.	PU
375ml	P1601	28
5L	P1602	4
10L	P1608	1
25L	P1603	1
200L	P1605	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

14.11.2017