

# Injector Dismantling Aid (IDA)

## Injector Dismantling Aid

### Product properties

To release jammed, problematic compounds in the engine and cylinder head area (such as injectors, spark and glow plugs, etc.) PRO-TEC Injector Dismantling Aid breaks corrosion and residues off the surface by extreme material cooling (-40 °C). The synthetic oil contains lubricious PTFE particles that can quickly and effectively penetrate the resulting microcracks and provide an easy and gentle removal.

- High-grade synthetic oil
- Cooling to -40 °C
- Lubricious PTFE particles – no residues, therefore no jamming or sticking
- Fat and acid free
- Infiltrates rust and displaces moisture
- Extreme capillary action
- 360° upside-down valve

### Area of application

Engine and cylinder head area

### Application

Shake product vigorously before use. Remove large contaminations manually. Apply product generously to the base of part to be removed (injector/cylinder head) and let work for 10-15 minutes. Repeat as needed. Remove loosened contaminants with compressed air.

### Consumption

Varies based on different applications

### Reaction time

approx. 10-15 minutes

### Technical data

Physical state: aerosol  
Colour: red/ silver grey  
Odour: characteristic  
Initial boiling point and boiling range: < -20 °C  
Flashpoint: < -20 °C  
Lower explosion limit: 0,6 Vol.-%  
Upper explosion limit: 10,8 Vol.-%  
Ignition temperature: > 200 °C  
Density at 68 °F: 0,63 g/cm<sup>3</sup>

Available sizes	Item no.	PU
400ml	P2250	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

06.02.2018