

White Grease (PTFE)

White Grease

Product properties

PRO-TEC White Grease guarantees an optimal long-term lubrication throughout the temperature range. The special formula contains Teflon which forms a centrifugal and high-pressure resistant protection layer that repels water, is resistant to heat and salt and reliably protects against corrosion.

Area of application

In the industry and workshop area e.g. for corroded hinges, bolted connections, brake linkages and components, door latches, hinges, gears, springs, bearings, rubber components, 'o' rings, striker plates, window regulators, sliding shackles etc.

Application

Shake well before use. Thoroughly clean the areas to be treated before application. Spray evenly onto the parts to be lubricated from a distance of 20-30 cm. Move lubricated parts for several seconds to ensure total coverage.

Consumption

Depending on the application

Technical data

Physical state: aerosol

Colour: white

Odour: characteristic

Lower explosion limit: 0,6 Vol.-%

Ignition temperature: > 250 °C

Density at 68 °F: 0,70 g/cm³

Water resistant

Available sizes	Item no.	PU
500ml	P2701	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

06.02.2018