



Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Diesel Anti Smoke

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti Smoke Additive

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, DiplChem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	
1.4. Emergency telephone	GBK GmbH: +49-(0)6132-84463 (24/7)	

1

number:

Further Information

Article Number: 33184, 33510, 33511, 33512, 33514

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Acute toxicity: Acute Tox. 4 Aspiration hazard: Asp. Tox. 1 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Harmful if swallowed. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics 2-Ethyl hexyl nitrate

Solvent naphtha (petroleum, gasoline), heavy aromatic

Signal word: **Pictograms:**



Hazard statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.





Diesel Anti Smoke

Revision date: 27.04.2018	Product code: 1331	Page 2 of 9
P260	Do not breathe vapour/aerosole.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.	
P331	Do NOT induce vomiting.	
P405	Store locked up.	
P501	Dispose of this material and its container to hazardous or special waste collection point.	
Special labelling of cert	tain mixtures	
EUH044	Risk of explosion if heated under confinement.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
2.3. Other hazards		

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Synthetic agent combinations Lubricants

Lubricants Multifunction Diesel Fuel Additive

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation	ion (EC) No. 1272/2008 [CLP]		
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes	s, Isoalkanes, Cyclics, < 2% Aromatic	cs	60 - < 80 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
27247-96-7	2-Ethyl hexyl nitrate			10 - < 25 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute To EUH066	ox. 4, Aquatic Chronic 2; H332 H312	H302 H411 EUH044	
68439-80-5	polyolefin amide alkylen amine			1 - < 5 %
	Aquatic Chronic 4; H413			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes . Subsequently wash off with: Water and soap.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.





Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 3 of 9

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible. After ingestion: Harmful: may cause lung damage if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Sand. Carbon dioxide (CO2). alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire. Beat down gas/vapours/mist with water spray. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear a self-contained breathing apparatus and chemical resistant suit.

Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Prevent spread over a wide area (e.g. by containment or oil barriers).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin. Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 4 of 9

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes. Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation. In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellow	
Odour:	characteristic	
Changes in the physical state		
Initial boiling point and boiling range:		200 - 210 °C
Flash point:		> 65 °C
Lower explosion limits:		> 0,6 vol. %
Upper explosion limits:		> 7,0 vol. %
Ignition temperature:		> 200 °C
Density (at 20 °C):		0,810 - 0,825 g/cm³
Water solubility:		insoluble
(at 20 °C)		
Solubility in other solvents Organic solvents		
2. Other information		

9.2. Other information

No data

SECTION 10: Stability and reactivity





Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 5 of 9

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix calculated

ATE (oral) 1923,1 mg/kg

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13,	n-Alkanes, I	soalkanes, C	Cyclics, < 2% Aromatics		
	oral	LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit		
	inhalative (4 h) gas	LC50	>5 ppm	Rat		
27247-96-7	2-Ethyl hexyl nitrate					
	oral	LD50 mg/kg	>9640	Rat		
	dermal	LD50 mg/kg	>4820	Rabbit		
	inhalative (1 h) vapour	LC50	4,6 mg/l	Rat		
	inhalative aerosol	ATE	1,5 mg/l			

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

Sensitising effects

no danger of sensitization.

SECTION 12: Ecological information

12.1. Toxicity





Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 6 of 9

CAS No	Chemical name	hemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64742-48-9	Hydrocarbons, C10-C13,	n-Alkanes, Is	oalkanes, C	≎yclics, <	2% Aromatics			
	Acute fish toxicity	LC50 mg/l	1000	96 h	Oncorhynchus mykiss			
	Acute algae toxicity	ErC50 mg/l	1000		Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50 mg/l	1000		Daphnia magna (Big water flea)			
27247-96-7	2-Ethyl hexyl nitrate							
	Acute fish toxicity	LC50	2 mg/l	96 h	Fish			
	Acute algae toxicity	ErC50 mg/l	1-10	72 h	Algae			
	Acute crustacea toxicity	EC50	>10 mg/l	48 h	Daphnia magna			

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water. Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Land transport (ADD/DID)

Container must be completely emptied. Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Revision date: 27.04.2018

Safety Data Sheet



according to Regulation (EC) No 1907/2006

Diesel Anti Smoke Product code: 1331

Page 7 of 9 Classification code: M6 Special Provisions: 274 335 375 601 Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 90 Tunnel restriction code: Inland waterways transport (ADN) UN 3082 14.1. UN number: 14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.3. Transport hazard class(es): 9 ||| 14.4. Packing group: 9 Hazard label: Classification code: M6 274 335 375 601 **Special Provisions:** Limited quantity: 5 L Excepted quantity: E1 Marine transport (IMDG) 14.1. UN number: UN 3082 14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.3. Transport hazard class(es): 9 14.4. Packing group: Ш Hazard label: 9 Marine pollutant: Р **Special Provisions:** 274, 335, 969 Limited quantity: 5 L Excepted quantity: E1 EmS: F-A, S-F Air transport (ICAO-TI/IATA-DGR) UN 3082 14.1. UN number: 14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.3. Transport hazard class(es): 9 Ш 14.4. Packing group: Hazard label: 9 A97 A158 A197

Special Provisions: Limited quantity Passenger:

30 kg G





	Diesel Anti Smoke	
Revision date: 27.04.2018	Product code: 1331	Page 8 of 9
Passenger LQ: Excepted quantity:	Y964 E1	
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	964 450 L 964 450 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	yes	72
Danger releasing substance:	Solvent naphtha (petroleum, gasoline), heavy arom. 2-Ethyl hexyl nitrate	
14.6. Special precautions for user No information available.		
14.7. Transport in bulk according to Annex No information available.	II of Marpol and the IBC Code	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixture	
EU regulatory information Restrictions on use (REACH, annex XVII Entry 28: Hydrocarbons, C10-C13, n-): Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	
Additional information Contains: > 30 % hydrocarbons, aliphatic. < 5 % hydrocarbons, aromatic.		
National regulatory information		
Water contaminating class (D):	1 - slightly water contaminating	

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.





Diesel Anti Smoke

Revision date: 27.04.2018

Product code: 1331

Page 9 of 9

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)