

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Autoprofi Cetane Booster

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Increase the cetane number.

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 43216

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Harmful if inhaled.

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

2-Ethyl hexyl nitrate

Signal word: Danger

Pictograms:



Hazard statements

H302+H332

Harmful if swallowed or if inhaled.

H304

May be fatal if swallowed and enters airways.

H411

Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 2 of 9

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe vapour/aerosole.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P312	Call a POISON CENTER/doctor if you feel unwell.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Special labelling of certain mixtures

EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Petroleum (Gasoline)
Additives

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			50 - < 70 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
27247-96-7	2-Ethyl hexyl nitrate			20 - < 50 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H332 H312 H302 H411 EUH044 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Move victim out of danger zone. Provide fresh air. Consult physician.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 3 of 9

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful by inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray. Sand. Foam. Carbon dioxide. dry extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No information available.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Contaminated fire-fighting water must not get into the sewerage network.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation.

Avoid contact with skin and eyes.

Do not breathe gas/fumes/vapour/spray.

Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: Sand Kieselguhr. Universal binding agent. Sawdust.

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of fumes/aerosols.

Do not breathe gas/fumes/vapour/spray.

Do not pierce, cut up or weld unclean container.

Advice on protection against fire and explosion

When hot, product develops flammable vapors.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Risk of explosion if heated under confinement.

7.2. Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 4 of 9

Requirements for storage rooms and vessels

Keep container tightly closed. Do not store at temperatures over: 50 °C
Provide for good ventilation, when develop aerosols/mist.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

hydrocarbons.
group 1
200 ml/m³ (ppm) 1000 mg/m³

Protective and hygiene measures

Avoid contact with skin, eyes and clothes.

Eye/face protection

Suitable eye protection: Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber).

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

Respiratory protection: not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	aromatic

Changes in the physical state

Initial boiling point and boiling range:	180 - 220 °C
Flash point:	> 65 °C
Lower explosion limits:	0,73 vol. %
Upper explosion limits:	6 vol. %
Ignition temperature:	> 200 °C
Density (at 20 °C):	0,83 - 0,84 g/cm ³
Water solubility:	insoluble

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 5 of 9

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

No decomposition when used as intended.

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products:

Carbon monoxide.

Carbon dioxide.

Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix calculated

ATE (oral) 1250,0 mg/kg; ATE (inhalative aerosol) 3,750 mg/l

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalative (4 h) gas	LC50 >5 ppm	Rat		
27247-96-7	2-Ethyl hexyl nitrate				
	oral	LD50 >9640 mg/kg	Rat		
	dermal	LD50 >4820 mg/kg	Rabbit		
	inhalative (1 h) vapour	LC50 4,6 mg/l	Rat		
	inhalative aerosol	ATE 1,5 mg/l			

Irritation and corrosivity

Irritant effect on the eye: irritant.

Irritant effect on the skin: Frequently or prolonged contact with skin may cause dermal irritation.

Carcinogenic/mutagenic/toxic effects for reproduction

No Carcinogenic, germ cell mutagen and reproduction effects

SECTION 12: Ecological information

12.1. Toxicity

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 6 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 mg/l	1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna (Big water flea)	
27247-96-7	2-Ethyl hexyl nitrate					
	Acute fish toxicity	LC50	2 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50 mg/l	1-10	72 h	Algae	
	Acute crustacea toxicity	EC50	>10 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

Product is partially biodegradable.

12.3. Bioaccumulative potential

Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Carry out under observation of official regulations covering a chemical/physical treatment plant.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Arrange about the exact waste code with the local waste disposal expert.

Waste disposal number of waste from residues/unused products

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Waste disposal number of used product

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Do not pierce, cut up or weld unclean container.

SECTION 14: Transport information

Land transport (ADR/RID)

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 7 of 9

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
2-Ethyl hexyl nitrate
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M6
Special Provisions: 274 335 375 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
2-Ethyl hexyl nitrate
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M6
Special Provisions: 274 335 375 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
2-Ethyl hexyl nitrate
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Marine pollutant: P
Special Provisions: 274, 335, 969
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 8 of 9

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
2-Ethyl hexyl nitrate

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9



Special Provisions: A97 A158 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: 2-Ethyl hexyl nitrate

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

Additional information

Contains:

> 30 % hydrocarbons, aliphatic.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H302	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

according to Regulation (EC) No 1907/2006

Autoprofi Cetane Booster

Revision date: 25.05.2018

Product code: 1695

Page 9 of 9

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)