

DPF Top Gun Cleaner

Product properties

DPF Top Gun Cleaner for compressed-air pistols solves and removes all soot deposition and residues without disassembly. Cleans gently and can be used on all aluminum, magnesium, zinc and cadmium parts. The product can be used perfectly for the latest generation of particle filters. Suitable for all closed particle filter systems.

Area of application

The product can be used perfectly for the latest generation of particle fiters. Suitable for all closed particle fiter systems.

Application

Spray over the probe-hole with the special probe in the direction of the particle filter. DPF Top Gun Cleaner is applicable to all closed particle filter systems. Check oil level before cleaning. In case of oil dilution by diesel necessarily perform an oil change. Do a test drive of at least 20 minutes. If regeneration does not start automatically by the engine electronic, start it with a garage probe.

Application with DPF Gun Flush

Consumption Depended on contamination

Reaction time

Works during application

Technical data

Physical state: liquid Colour: clear/colourless Odour: characteristic pH-Value (at 68 °F): 10 - 11,5 Melting point: > 0 °C Initial boiling point and boiling range: > 98 °C Flashpoint: > 65 °C Density at 68 °F: 0,99 - 1,1 g/cm³ Water solubility: miscible Viscosity / kinematic (at 104 °F): ~1,0 mm²/s

Available	Item no.	PU
sizes		
1000ml	33481	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



CTP GmbH Saalfelder Straße 35 h 07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de 26.06.2018