



according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bike Line Fuel Line Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Fuel Systems

1.3. Details of the supplier of the safety data sheet

Company name: CTP GmbH

Street: Saalfelder Strasse 35h
Place: D-07338 Leutenberg

Telephone: +49 (0)36734 230-0 Telefax: +49 (0)36734 230-22

e-mail: msds@bluechemgroup.com

Contact person: Jens Moeller, Dipl.-Chem. Telephone: +49 (0)36734 230-19

Internet: www.bluechemgroup.com

1.4. Emergency telephone GBK GmbH: +49-(0)6132-84463 (24/7)

number:

Further Information

Article Number: 3011

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2 Acute toxicity: Acute Tox. 4 Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3
Specific target organ toxicity - single exposure: STOT SE 3
Specific target organ toxicity - repeated exposure: STOT RE 2
Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Harmful if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

xylene

propan-2-ol; isopropyl alcohol; isopropanol

acetone; propan-2-one; propanone

Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 2 of 11

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe Gas/Vapour/aerosole.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Surface tension compounds Detergents, Dispersants Synthetic agent combinations Anti wear agents not classified





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 3 of 11

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regula			
1330-20-7	xylene			30 - < 35 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 1; H226 H332 H312 H315 H		rit. 2, STOT SE 3, STOT RE 2, Asp.	
67-63-0	propan-2-ol; isopropyl alcohol; iso	propanol		20 - < 25 %
	200-661-7		01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SI	E 3; H225 H319 H336		
67-64-1	acetone; propan-2-one; propanor	20 - < 25 %		
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SI	E 3; H225 H319 H336 EU	JH066	
64742-48-9	Hydrocarbons, C9-C11, n-Alkane	< 2% Aromates	15 - < 20 %	
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. To			
64742-47-8	Hydrocarbons, C9-C11, Isoalkane	5 - < 10 %		
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. To			
37205-87-1	phenole, ethoxylised			1 - < 5 %
	Acute Tox. 4, Eye Dam. 1, Aquati	c Chronic 2; H302 H318	H411	
N/A	Poly[oxy(1,2-butanediyl)], .alpha. C13-rich (Polyetheramines)	1 - < 5 %		
	Aquatic Chronic 2; H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 4 of 11

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 5 of 11

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Packaging materials: metal.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	-	End of shift at end of workweek
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: red
Odour: aromatic

Changes in the physical state

Initial boiling point and boiling range: 110 - 116 °C





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner Revision date: 17.12.2018 Product code: 650 Page 6 of 11					
(CVICION GAIO. 17.12.2010	1104401.000	- 1 ago o or 1			
Flash point:	-5 °C				
Lower explosion limits:	0,6 vol. %				
Upper explosion limits:	12 vol. %				
Ignition temperature:	> 200 °C				
Vapour pressure: (at 20 °C)	20 hPa				
Density (at 20 °C):	0.78-0.82 g/cm³				
Water solubility: (at 20 °C)	insoluble				
Solubility in other solvents Organic solvents					

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents.

acid, concentrated.

Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix calculated

ATE (inhalation aerosol) 4,795 mg/l





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 7 of 11

Acute toxicity

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1330-20-7	xylene						
	oral	LD50 mg/kg	4300	Rat			
	dermal	LD50 mg/kg	3200	Rabbit			
	inhalation (4 h) vapour	LC50	21,7 mg/l	Rat			
	inhalation aerosol	ATE	1,5 mg/l				
67-63-0	propan-2-ol; isopropyl ald	cohol; isopr	opanol				
	oral	LD50 mg/kg	5280	Rat			
	dermal	LD50 mg/kg	12800	Rabbit			
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat			
67-64-1	acetone; propan-2-one; p	oropanone					
	oral	LD50 mg/kg	5800	Rat	RTECS		
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID		
	inhalation (4 h) vapour	LC50	76 mg/l	Rat			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates						
	oral	LD50 mg/kg	>5000	Rat			
	dermal	LD50 mg/kg	>5000	Rabbit			
	inhalation (4 h) aerosol	LC50	>5 mg/l	Rat			
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalcanes, < 2% Aromates						
	oral	LD50 mg/kg	>5000	Rat			
	dermal	LD50 mg/kg	>5000	Rabbit			
	inhalation (4 h) aerosol	LC50	>5 mg/l	Rat			
37205-87-1	phenole, ethoxylised						
	oral	LD50 mg/kg	2000	Rat			
N/A	Poly[oxy(1,2-butanediyl)], .alpha(3-aminopropyl)gammahydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)						
	oral	LD50 mg/kg	>5000	Rat			
	dermal	LD50 mg/kg	>2000	Rabbit			

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 8 of 11

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name								
-	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
1330-20-7	xylene								
	Acute fish toxicity	LC50 mg/l	26,7	96 h	Pimephales promelas				
67-63-0	propan-2-ol; isopropyl alc	ohol; isopro	panol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae				
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna				
67-64-1	acetone; propan-2-one; p	ropanone							
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss				
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna				
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates								
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss				
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna				
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalcanes, < 2% Aromates								
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss				
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna				
37205-87-1	phenole, ethoxylised								
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Brachydanio rerio				
	Acute algae toxicity	ErC50 mg/l	1-10	72 h	Scenedesmus subspicatus				
N/A	Poly[oxy(1,2-butanediyl)], .alpha(3-aminopropyl)gammahydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)								
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Fish				
	Acute algae toxicity	ErC50 mg/l	10-100	72 h	Algae				

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 9 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 10 of 11



Classification code: F1

Special Provisions: 274 601 640D

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

274

1 L

Excepted quantity:

E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture





according to Regulation (EC) No 1907/2006

Bike Line Fuel Line Cleaner

Revision date: 17.12.2018 Product code: 650 Page 11 of 11

EU regulatory information

Authorisations (REACH, annex XIV):

phenole, ethoxylised

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates

Entry 46a: phenole, ethoxylised

Additional information

Contains:

15 - 30 % hydrocarbons, aliphatic.

> 30 % hydrocarbons, aromatic.

< 5 % phenols and halogenated phenols

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)