



Revision date: 21.09.2018	Product code: 139	on Flush
	Product code: 139	15 Page 1 of
SECTION 1: Identification of	f the substance/mixture and of the com	npany/undertaking
		·Par. J. co ac ca
1.1. Product identifier		
Automatic Transmission Flu	Jsh	
1.2. Relevant identified uses of	f the substance or mixture and uses advise	ed against
Use of the substance/mixtu	re	
Cleaning agent		
1.3. Details of the supplier of the	<u>ne safety data sheet</u>	
Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	Telephone, 10 (0)26724 220 40
Contact person: Internet:	Jens Moeller, DiplChem. www.bluechemgroup.com	Telephone:+49 (0)36734 230-19
	C .	
1.4. Emergency telephone	GBK GmbH: +49-(0)6132-84463 (24	+//)
SECTION 2: Hazards identif	ication	
2.1. Classification of the subst		
Regulation (EC) No. 1272/200	8	
Hazard catedories.		
Hazard categories: Aspiration hazard: Asp. T	ōx 1	
Aspiration hazard: Asp. T		
Aspiration hazard: Asp. T Respiratory or skin sensit		
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements:	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3 l and enters airways.	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3 l and enters airways. in reaction.	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3 l and enters airways. in reaction.	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3 l and enters airways. in reaction.	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit	tisation: Skin Sens. 1 e environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects.	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labo	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquation Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life with 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labor Hydrocarbons, C10-C13,	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma	atics
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquation Hazard Statements: May be fatal if swallowed May cause an allergic skin Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labor Hydrocarbons, C10-C13, mixture of hydrocarbons	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labe Hydrocarbons, C10-C13, mixture of hydrocarbons Amines, C12-14-tert-alky	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10 l, reaction products with O,O-di-C1-14-alkyl h	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labe Hydrocarbons, C10-C13, mixture of hydrocarbons Amines, C12-14-tert-alky	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labe Hydrocarbons, C10-C13, mixture of hydrocarbons Amines, C12-14-tert-alky	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10 l, reaction products with O,O-di-C1-14-alkyl h	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labe Hydrocarbons, C10-C13, mixture of hydrocarbons Amines, C12-14-tert-alky Signal word: Da	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10 l, reaction products with O,O-di-C1-14-alkyl h	
Aspiration hazard: Asp. T Respiratory or skin sensit Hazardous to the aquatic Hazard Statements: May be fatal if swallowed May cause an allergic ski Harmful to aquatic life wit 2.2. Label elements Regulation (EC) No. 1272/200 Hazard components for labe Hydrocarbons, C10-C13, mixture of hydrocarbons Amines, C12-14-tert-alky Signal word: Da	tisation: Skin Sens. 1 c environment: Aquatic Chronic 3 l and enters airways. in reaction. th long lasting effects. 8 elling n-Alkanes, Isoalkanes, Cyclics, < 2% Aroma (aromatic) C9-C10 l, reaction products with O,O-di-C1-14-alkyl h	

Hazard statements

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.





Automatic Transmission Flush

Revision date: 21.09.2018	Product code: 1395	Page 2 of 8		
P102	Keep out of reach of children.			
P260	Do not breathe vapour/aerosole.			
P270	Do not eat, drink or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves.			
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.			
P331	Do NOT induce vomiting.			
P302+P352	IF ON SKIN: Wash with plenty of water.			
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
P405	Store locked up.			
P501	Dispose of this material and its container to hazardous or special waste collection point.			
Special labelling of cert	ain mixtures			
EUH066	Repeated exposure may cause skin dryness or cracking.			

EUH066 2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Detergents, Dispersants Anti Friction Components Synthetic agent combinations Solvent mixture Additives ashless

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulat	on (EC) No. 1272/2008 [CL	.P]	
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes	s, Isoalkanes, Cyclics, < 2%	Aromatics	75 - < 80 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066		·	
64742-95-6	mixture of hydrocarbons (aromatic)	C9-C10		15 - < 20 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE H411 EUH066			
71888-91-0	Amines, C12-14-tert-alkyl, reaction phosphorodithioate	products with O,O-di-C1-14	4-alkyl hydrogen	5 - < 10 %
	276-159-7		01-2120770937-38	
	Skin Sens. 1, Aquatic Chronic 2; H			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes . Subsequently wash off with: Water and soap.





Automatic Transmission Flush

Revision date: 21.09.2018

Product code: 1395

Page 3 of 8

Seek medical attention if problems persist.

After contact with eyes

Remove contact lenses.

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. After ingestion of absorption substances: Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Sand. Carbon dioxide (CO2). alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire. Beat down gas/vapours/mist with water spray. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear a self-contained breathing apparatus and chemical resistant suit. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray. Do not empty into drains or the aquatic environment. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Prevent spread over a wide area (e.g. by containment or oil barriers).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling





according to Regulation (EC) No 1907/2006

Automatic Transmission Flush

Revision date: 21.09.2018

Product code: 1395

Page 4 of 8

Advice on safe handling

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin. Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Do not store at temperatures over: 50 °C Take precautionary measures against static discharges.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes. Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

Provide for good ventilation, when develop aerosols/mist. In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	liquid yellow aromatic	
Changes in the physical state Initial boiling point and boiling range:	18	30 - 220 °C
Flash point:		63 °C
Lower explosion limits: Upper explosion limits:		
Ignition temperature:		> 200 °C





according to Regulation (EC) No 1907/2006

Automatic Transmission Flush				
Revision date: 21.09.2018	Product code: 1395	Page 5 of 8		
Vapour pressure: (at 20 °C)	20 hPa			
Density (at 20 °C):	0.82 - 0.90 g/cm³			
Water solubility: (at 20 °C)	insoluble			
Solubility in other solvents Organic solvents				
9.2. Other information				
No data				

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away. No decomposition when used as intended.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13,	n-Alkanes, Is	oalkanes, C	Cyclics, < 2% Aromatics		
	oral	LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit		
	inhalation (4 h) gas	LC50	>5 ppm	Rat		
64742-95-6	mixture of hydrocarbons (aromatic) C9-C10					
	oral	LD50 mg/kg	>3000	Rat		
	dermal	LD50 mg/kg	>3160	Rat		
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate					
	oral	LD50 mg/kg	>2000	Rat		





according to Regulation (EC) No 1907/2006

Automatic Transmission Flush

Revision date: 21.09.2018

Product code: 1395

Page 6 of 8

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

Sensitising effects

no danger of sensitization.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, r	n-Alkanes, Isoal	kanes, C	yclics, <	2% Aromatics		
	Acute fish toxicity LC50 1000 mg/l		96 h	Oncorhynchus mykiss			
	Acute algae toxicity	ErC50 10 mg/l	000	. –	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 10 mg/l	000		Daphnia magna (Big water flea)		
64742-95-6	2-95-6 mixture of hydrocarbons (aromatic) C9-C10						
	Acute fish toxicity	LC50 1 mg/l	- 10	96 h	Daphnia magna		
71888-91-0	-91-0 Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate						
	Acute fish toxicity	LC50 2, mg/l	55	96 h	Brachydanio rerio		
	Acute crustacea toxicity	EL50 4, mg/l	90	48 h	Daphnia magna		

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Container must be completely emptied.





according to Regulation (EC) No 1907/2006

Automatic Transmission Flush

Revision date: 21.09.2018

Product code: 1395

Page 7 of 8

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Other applicable information (land transport) No dangerous good in sense of this transport regulation. Inland waterways transport (ADN) Other applicable information (inland waterways transport) No dangerous good in sense of this transport regulation. Marine transport (IMDG) Other applicable information (marine transport) No dangerous good in sense of this transport regulation. Air transport (ICAO-TI/IATA-DGR) Other applicable information (air transport) No dangerous good in sense of this transport regulation. 14.5. Environmental hazards **ENVIRONMENTALLY HAZARDOUS:** no 14.6. Special precautions for user No information available. 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No information available. **SECTION 15: Regulatory information** 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulatory information Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics; mixture of hydrocarbons (aromatic) C9-C10

Additional information

Contains:

15 - 30 % hydrocarbons, aromatic.> 30% hydrocarbons, aliphatic.5 - 10 % phosphates

National regulatory information

Water contaminating class (D):

2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information





Automatic Transmission Flush

Revision date: 21.09.2018

Product code: 1395

Page 8 of 8

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure			
Asp. Tox. 1; H304	Calculation method			
Skin Sens. 1; H317	Calculation method			
Aquatic Chronic 3; H412	Calculation method			

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)