

## MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

MOS 2 Rust Remover, Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cleaning agent.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

#### 1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

#### Further Information

Article Number: 22052

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Kerosene (Mineral Oil), hydrosulfurised

Signal word: Danger

Pictograms:



##### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.



## Safety Data Sheet

**bluechem**   
**GROUP**

according to Regulation (EC) No 1907/2006

### MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 2 of 10

#### Precautionary statements

- |           |  |
|-----------|--|
| P101      | If medical advice is needed, have product container or label at hand.                          |
| P102      | Keep out of reach of children.   |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211      | Do not spray on an open flame or other ignition source.  |
| P251      | Do not pierce or burn, even after use.   |
| P261      | Avoid breathing aerosole.  |
| P271      | Use only outdoors or in a well-ventilated area.  |
| P280      | Wear protective gloves and eye/face protection.  |
| P302+P352 | IF ON SKIN: Wash with plenty of water.   |
| P312      | Call a POISON CENTER/doctor if you feel unwell.  |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.                   |
| P501      | Dispose of this material and its container to hazardous or special waste collection point.     |

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

alcoholes  
Corrosion inhibitors.

## MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 3 of 10

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			10 - 20 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
(64742-81-0)	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)			10 - 20 %
	925-653-7		01-2119458869-15	
	Asp. Tox. 1, Aquatic Chronic 3; H304 H412 EUH066			
64742-81-0	Kerosene (Mineral Oil), hydrosulfurised			10 - 20 %
	265-184-9		01-2119462828-25	
	Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H315 H336 H304 H411			
64742-53-6	Distillates, hydrotreated light, naphthenic			10 - 20 %
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			
74-98-6	propane			10 - 20 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
75-28-5	isobutane			10 - 20 %
	200-857-2		01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
106-97-8	Butane			2,5 - 10 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether			1 - 2,5 %
	203-905-0		01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down.  
Change contaminated clothing.

#### After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.  
In case of skin irritation, seek medical treatment.

#### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Consult physician.

**MOS 2 Rust Remover, Aerosol**

Revision date: 20.05.2019

Product code: 301

Page 4 of 10

**4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

**4.3. Indication of any immediate medical attention and special treatment needed**

The following symptoms may occur:

unconsciousness. Intoxication. vomiting. drowsiness. Headache.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water fog. alcohol resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Swims on the water. Vapours are heavier than air and will spread at floor level.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes.

Do not breathe gas/fumes/vapour/spray.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

**6.4. Reference to other sections**

Explosive. Vapours may form explosive mixtures with air.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Keep only in the original container in a cool, well-ventilated place.

Have to care for a good Ventilation at workplace.

**Advice on protection against fire and explosion**

Vapours may form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C

Heating causes rise in pressure with risk of bursting.

**7.3. Specific end use(s)**

No information available.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 5 of 10

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

#### Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

#### Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

#### Respiratory protection

Provide for good ventilation, when develop aerosols/mist.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	yellowish
Odour:	characteristic

#### Changes in the physical state

Ignition temperature:	> 200 °C
Density (at 20 °C):	0,705 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble
Solvent content:	85,5 %

### 9.2. Other information

No data

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

## MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 6 of 10

### 10.2. Chemical stability

No decomposition when used as intended.

### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4. Conditions to avoid

Do not store at temperatures over: 50 °C

Keep away from heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No dangerous reactions are known.

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 mg/kg	> 5000	Rat	
	dermal	LD50 mg/kg	> 5000	Rabbit	
	inhalation (4 h) gas	LC50	>5 ppm	Rat	
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether				
	oral	LD50 mg/kg	1300	Rat	
	dermal	ATE mg/kg	1100		
	inhalation (4 h) vapour	LC50	>10 mg/l	Guinea pig	
	inhalation aerosol	ATE	1,5 mg/l		

#### Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 mg/l	1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna (Big water flea)	

## MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 7 of 10

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
75-28-5	isobutane	2,8

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

No information available.

### 12.6. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Arrange about the exact waste code with the local waste disposal expert.

Do not dispose with household waste.

#### Contaminated packaging

Dispose of waste according to applicable legislation. Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

## SECTION 14: Transport information

### Land transport (ADR/RID)

#### 14.1. UN number:

UN 1950

#### 14.2. UN proper shipping name:

AEROSOLS  
Propane/butane-mixture

#### 14.3. Transport hazard class(es):

2

#### 14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Hazard No:

-

Tunnel restriction code:

D

## MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 8 of 10

### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: -  
 Special Provisions: 63, 190, 277, 327, 344, 381, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
 Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

### 14.5. Environmental hazards





## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### MOS 2 Rust Remover, Aerosol

Revision date: 20.05.2019

Product code: 301

Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: no

#### **14.6. Special precautions for user**

No information available.

#### **14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics; Distillates, hydrotreated light, naphthenic; isobutane; Butane

2004/42/EC (VOC): 602,6 g/l

##### **Additional information**

Contains:

> 30 % hydrocarbons, aliphatic.

##### **National regulatory information**

Water contaminating class (D): 2 - clearly water contaminating

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,14,15.

#### **Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

#### **Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.



## Safety Data Sheet

**bluechem**   
**GROUP**

according to Regulation (EC) No 1907/2006

### **MOS 2 Rust Remover, Aerosol**

Revision date: 20.05.2019

Product code: 301

Page 10 of 10

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*