

Diesel Organic Cleaner

Product properties

High-performance concentrate based on special surface-active agents for the prevention of bacteria, yeasts, algae and fungi in diesel fuels, which cause sludge formation in the fuel tank – diesel contamination.

The application preemptively deprives microorganisms from replicating and prevents any new formation. As a result, this treatment further prevents the fuel filter from becoming blocked.

Benefits:

- Prevents against bacteria, yeasts, algae and fungi
- Prevents blockage of the fuel filter
- Improves cold start performance
- Clean and powerful combustion
- Improves the engine performance
- Cleans fuel system and filter
- Protects against corrosion

Area of application

Suitable for all diesel applications with addition to the fuel tank. Ideal for bio-diesel as well. Specially recommended for storage tanks, boats, agricultural machinery and caravans.

Application

Add regularly every 3-4 months to the diesel system. Specially recommended before long term or seasonal vehicle storage. In case of severe contamination of the diesel fuel, it is necessary to clean the tank and fuel system before treatment!

Consumption

375 ml treats up to 80 liters of diesel fuel. Mixing ratio of 1:200

Reaction time

Works during normal operating conditions.

Technical data

Physical state: liquid

Colour: colourless cloudy

Odour: characteristic

Initial boiling point and boiling range: 82 °C

Flashpoint: 12 °C DIN 51755

Lower explosion limit: 2 Vol.-%

Upper explosion limit: 12 Vol.-%

Density at 68 °F: 0,795 g/cm³ DIN 51757

Available sizes	Item no.	PU
375ml	P1293	28



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

11.07.2019