



# Diesel Organic Cleaner

Revision date: 20.06.2019

Product code: 2195

Page 1 of 8

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Diesel Organic Cleaner

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Cleaning agent for Fuel Systems

### 1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone: e-mail:	+49 (0)36734 230-0 msds@bluechemgroup.com	Telefax:+49 (0)36734 230-22
Contact person: Internet:	Jens Moeller, DiplChem. www.bluechemgroup.com	Telephone:+49 (0)36734 230-19
1.4. Emergency telephone	GBK GmbH: +49-(0)6132-84463 (24/7)	

### number:

Further Information Article Number: 1293

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

# 2.2. Label elements

### Regulation (EC) No. 1272/2008

# Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Danger

Signal word:

**Pictograms:** 



# Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Precautionary statements

oouullonaly olulonion	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No





Revision date: 20.06.2019	Product code: 2195	Page 2 of 8				
	smoking.					
P233	Keep container tightly closed.					
P271	Use only outdoors or in a well-ventilated area.					
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.					
P501	Dispose of this material and its container to hazardous or special waste collection point.					

No information available.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Hazardous components

CAS No	Chemical name	Chemical name					
	EC No	Index No					
	GHS Classification	GHS Classification					
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	200-661-7		01-2119457558-25				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336						
69011-36-5	isotridecanole, ethoxylised			3 - 8 %			
	931-138-8						
	Acute Tox. 4, Eye Dam. 1; H302 H318						

Full text of H and EUH statements: see section 16.

### Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % non-ionic surfactants.

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### General information

Remove contaminated, saturated clothing immediately.

#### After inhalation

Following inhalation: Move victim to fresh air. Consult physician. In case of respiratory tract irritation, consult a physician.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical attention if problems persist.

### After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an opthalmologist.

# After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Consult physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible. Vapours may cause drowsiness and dizziness.

# 4.3. Indication of any immediate medical attention and special treatment needed



# Safety Data Sheet



according to Regulation (EC) No 1907/2006

# **Diesel Organic Cleaner**

Revision date: 20.06.2019

Product code: 2195

Page 3 of 8

After ingestion of absorption substances: Give activated carbon, in order to reduce the resorption in the gastro-enteric tract.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder.

### 5.2. Special hazards arising from the substance or mixture

Cool endangered container in case of fire. Heating causes rise in pressure with risk of bursting.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment. Provide adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

# 6.4. Reference to other sections

No data

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation. Avoid contact with skin and eyes.

### Advice on protection against fire and explosion

Take precautionary measures against static discharges.Keep away from sources of ignition - No smoking. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from moisture.

# 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Revision No: 3,0





# **Diesel Organic Cleaner**

Revision date: 20.06.2019

Product code: 2195

Page 4 of 8

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

# **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	-	End of shift at end of workweek

# 8.2. Exposure controls

# Protective and hygiene measures

Provide adequate ventilation.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

When using do not eat, drink or smoke.

Protect skin by using skin protective cream.

### Eye/face protection

Tightly sealed safety glasses.

# Hand protection

Suitable material: Butyl rubber. FKM (Fluoroelastomer (Viton)). Material thickness: 0.4 – 0.5 mm penetration time >= 480 min For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### **Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist generation. Wear suitable breathing apparatus (filter typ ABEK).

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid colourless cloudy		
Odour:	product-specific		
			Test method
pH-Value:		not applicable	
Changes in the physical state			
Initial boiling point and boiling range:		82 °C	
Flash point:		12 °C	DIN 51755
Lower explosion limits:		2 vol. %	
Upper explosion limits:		12 vol. %	
Auto-ignition temperature			
Gas:		425 °C	
Density (at 20 °C):		0,795 g/cm³	DIN 51757





2,5 mPa·s DIN 53015

according to Regulation (EC) No 1907/2006

# **Diesel Organic Cleaner**

Revision date: 20.06.2019

Product code: 2195

Page 5 of 8

Viscosity / dynamic: (at 20 °C)

### 9.2. Other information

No data

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

# 10.2. Chemical stability

No decomposition when used as intended.

### 10.3. Possibility of hazardous reactions

Reacts violently with: Oxidizing agents, strong.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

None

thermal decomposition: standard pressure decomposition distillable Reacts violently with: Oxidizing agents, strong.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity

Vapours may cause drowsiness and dizziness.

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
67-63-0	propan-2-ol; isopropyl alc	propan-2-ol; isopropyl alcohol; isopropanol						
	oral	LD50 mg/kg	5280	Rat				
	dermal	LD50 mg/kg	12800	Rabbit				
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat				
69011-36-5	isotridecanole, ethoxylise	isotridecanole, ethoxylised						
	oral	LD50 mg/kg	>2000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				

### Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

# **SECTION 12: Ecological information**

# 12.1. Toxicity





# **Diesel Organic Cleaner**

Revision date: 20.06.2019

Product code: 2195

Page 6 of 8

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alc	ohol; isoprop	anol				
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae		
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna		
69011-36-5							
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 mg/l	1-10	72 h	Fish		
	Acute crustacea toxicity	EC50 mg/l	1-10	48 h	Daphnia magna		

# 12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

CAS No	Chemical name						
	Method Value d Source						
	Evaluation						
69011-36-5	isotridecanole, ethoxylised						
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28				
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28				

# 12.3. Bioaccumulative potential

No information available.

# 12.4. Mobility in soil

No information available.

# 12.5. Results of PBT and vPvB assessment

No information available.

### 12.6. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### Advice on disposal

Carry out a burning of harzardous waste according to official regulations. For this product, the waste identity number according to the European waste catalogue cannot be defined because the designated use by the consumer allows the classification first. Arrange about the exact waste code with the local waste disposal expert.

### **SECTION 14: Transport information**

Land transport (ADR/RID)	
14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II



# Safety Data Sheet



according to Regulation (EC) No 1907/2006

Revision date: 20.06.2019	Diesel Organic Cleaner Product code: 2195	Page 7 of 8
Hazard label:	3	
Classification code:	F1	
Special Provisions:	601	
Limited quantity:	1L	
Excepted quantity: Transport category:	E2 2	
Hazard No:	33	
Tunnel restriction code:	D/E	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN 1219	
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	ll	
Hazard label:	3	
Classification code:	F1	
Special Provisions:	601	
Limited quantity: Excepted quantity:	1 L E2	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1219	
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Marine pollutant:	-	
Special Provisions:	-	
Limited quantity:	1 L E2	
Excepted quantity: EmS:	EZ F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1219	
14.2. UN proper shipping name:	Isopropyl alcohol	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	





Diesel Organic Cleaner			
Revision date: 20.06.2019	Product code: 2195	Page 8 of 8	
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity:	A180 1 L Y341 E2		
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	353 5 L 364 60 L		
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	no		
<b>14.6. Special precautions for user</b> No information available.			
<b>14.7. Transport in bulk according to Annex</b> No information available.	II of Marpol and the IBC Code		
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
EU regulatory information			
Additional information Contains: 5 - 15 % nonionic tensides			
National regulatory information			
Water contaminating class (D):	1 - slightly water contaminating		
15.2. Chemical safety assessment Chemical safety assessments for substances in this mixture were not carried out.			

# **SECTION 16: Other information**

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

### Relevant H and EUH statements (number and full text)

- H225 Highly flammable liquid and vapour.
- H302Harmful if swallowed.H318Causes serious eye damage.H319Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

# **Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product

properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

# (The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)