



according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Diesel Organic Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Fuel Systems

1.3. Details of the supplier of the safety data sheet

Company name: CTP GmbH

Street: Saalfelder Strasse 35h
Place: D-07338 Leutenberg

Telephone: +49 (0)36734 230-0 Telefax: +49 (0)36734 230-22

e-mail: msds@bluechemgroup.com

Contact person: Jens Moeller, Dipl.-Chem. Telephone: +49 (0)36734 230-19

Internet: www.bluechemgroup.com

1.4. Emergency telephone GBK GmbH: +49-(0)6132-84463 (24/7)

number:

Further Information

Article Number: 33650

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 2 of 8

smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	200-661-7		01-2119457558-25		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
69011-36-5	isotridecanole, ethoxylised				
	931-138-8				
	Acute Tox. 4, Eye Dam. 1; H302 H318				

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % non-ionic surfactants.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Following inhalation: Move victim to fresh air. Consult physician.

In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Seek medical attention if problems persist.

After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an opthalmologist.

After ingestion

Rinse mouth thoroughly with water.

Let water be drunken in little sips (dilution effect).

Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 3 of 8

After ingestion of absorption substances:

Give activated carbon, in order to reduce the resorption in the gastro-enteric tract.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog.

alcohol resistant foam.

Carbon dioxide (CO2).

Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Cool endangered container in case of fire.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Provide adequate ventilation.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed containers for disposal.

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges . Keep away from sources of ignition - No smoking.

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep away from moisture.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Protective and hygiene measures

Provide adequate ventilation.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

When using do not eat, drink or smoke.

Protect skin by using skin protective cream.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Suitable material: Butyl rubber. FKM (Fluoroelastomer (Viton)).

Material thickness: 0.4 - 0.5 mm penetration time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist generation.

Wear suitable breathing apparatus (filter typ ABEK).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: colourless cloudy
Odour: product-specific

Test method

pH-Value: not applicable

Changes in the physical state

Initial boiling point and boiling range: 82 °C

Flash point: 12 °C DIN 51755

Lower explosion limits: 2 vol. % Upper explosion limits: 12 vol. %

Auto-ignition temperature

Gas: 425 °C

Density (at 20 °C): 0,795 g/cm³ DIN 51757

Viscosity / dynamic: 2,5 mPa·s DIN 53015

(at 20 °C)

9.2. Other information

No data

SECTION 10: Stability and reactivity

Revision No: 3,0 GB - EN Print date: 20.06.2019





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 5 of 8

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

Reacts violently with: Oxidizing agents, strong.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

none

thermal decomposition: standard pressure decomposition distillable

Reacts violently with: Oxidizing agents, strong.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Vapours may cause drowsiness and dizziness.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-63-0	propan-2-ol; isopropyl al	propan-2-ol; isopropyl alcohol; isopropanol						
	oral	LD50 mg/kg	5280	Rat				
	dermal	LD50 mg/kg	12800	Rabbit				
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat				
69011-36-5	isotridecanole, ethoxylised							
	oral	LD50 mg/kg	>2000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

SECTION 12: Ecological information

12.1. Toxicity





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 6 of 8

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae		
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna		
69011-36-5	isotridecanole, ethoxylised						
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 mg/l	1-10	72 h	Fish		
	Acute crustacea toxicity	EC50 mg/l	1-10	48 h	Daphnia magna		

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

CAS No	Chemical name				
CAO NO	Chemical name				
	Method	Value	d	Source	
	Evaluation				
69011-36-5	isotridecanole, ethoxylised				
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28		
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28		

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Carry out a burning of harzardous waste according to official regulations.

For this product, the waste identity number according to the European waste catalogue can not be defined because the designated use by the consumer allows the classification first.

Arrange about the exact waste code with the local waste disposal expert.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es): 3
14.4. Packing group: |





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 7 of 8

Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1219

14.2. UN proper shipping name: Isopropyl alcohol

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



A180

Special Provisions:





according to Regulation (EC) No 1907/2006

Diesel Organic Cleaner

Revision date: 20.06.2019 Product code: 2244 Page 8 of 8

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Contains:

5 - 15 % nonionic tensides

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)