

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Autoprofi Engine Oil Stop Leak

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Stops losses of oil in diesel- and gasoline engines.

Oil Performance Improver

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number: GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 43223

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate

Signal word: Warning

Pictograms:



Hazard statements

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 2 of 7

P333+P313
P501

If skin irritation or rash occurs: Get medical advice/attention.
Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Additives
Inhibitors
Preventing agent
Mineral oils

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate			10 - < 15 %
	276-159-7		01-2120770937-38	
	Flam. Liq. 3, Skin Sens. 1, Aquatic Chronic 2; H226 H317 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .
Subsequently wash off with: Water and soap.
Seek medical attention if problems persist.

After contact with eyes

Remove contact lenses.
Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

After ingestion

Rinse mouth thoroughly with water.
Do NOT induce vomiting.
Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Sand.
Carbon dioxide (CO2).
Water spray.

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 3 of 7

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Beat down gas/vapours/mist with water spray.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear a self-contained breathing apparatus and chemical resistant suit.

High skid risk because of leaking or spilled product.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

The substance should only be handled in closed apparatus or systems.

Avoid contact with skin and eyes.

Avoid oil mist

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Do not store at temperatures over: 50 °C

Hints on joint storage

Should be stored separately from oxidizing agents.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing

Avoid contact with skin and eyes.

Keep away from food, drink and animal feeding stuffs.

When using do not eat, drink or smoke.

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 4 of 7

Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	viscous
Colour:	brown
Odour:	mild

Changes in the physical state

Flash point: > 100 °C

Lower explosion limits:

Upper explosion limits:

Density (at 20 °C): 0.89 - 0.92 g/cm³

Water solubility:
(at 20 °C) insoluble

Solubility in other solvents

Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

No decomposition when used as intended.

Keep at temperature not exceeding 50 °C.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 5 of 7

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate				
	oral	LD50 mg/kg	>2000	Rat	

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

Sensitising effects

no danger of sensitization.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate					
	Acute fish toxicity	LC50 mg/l	2,55	96 h	Brachydanio rerio	
	Acute crustacea toxicity	EL50 mg/l	4,90	48 h	Daphnia magna	

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.
Do not empty into drains or the aquatic environment.
Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Container must be completely emptied.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

-

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 6 of 7

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Contains:

5 - 15 % phosphates

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

Autoprofi Engine Oil Stop Leak

Revision date: 31.07.2019

Product code: 1581

Page 7 of 7

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)