

# Fuel System Water Remover

## Product properties

Binds and reliably removes condensed water and moisture from the entire fuel system. Protects against rust and corrosion and increases the lifespan of the engine. Ensures a clean and powerful combustion, improves engine running and cold starting performance and optimises exhaust emission. Prevents ice formation.

## Area of application

For all petrol and diesel powered engines.

## Application

Add every 3-4 months to the fuel system before filling up.

Caution: Cleaning fluid – no fuel substitute! Flammable. Harmful: may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. If swallowed, seek medical advice immediately and show this container or label. Keep out of reach of children.

## Consumption

300 ml sufficient for 60 – 80 litres petrol fuel

## Reaction time

Works during operation

## Technical data

Physical state: liquid

Colour: violet

Odour: aromatic

Initial boiling point and boiling range: 145 - 200 °C

Flashpoint: 35 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 6,5 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 4 hPa

Density at 68 °F: 0.78-0.82 g/cm<sup>3</sup>

Water resistant

Available sizes	Item no.	PU
300ml	33068	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.