

Easy Gear

Product properties

The highly effective anti-friction barrier seals all the internal surfaces of engines and equipment. Remarkably reduces wear and tear and guarantees optimized lubrication throughout the temperature range. Keeps seals, shaft seals and "o" rings soft and supple. Easy Gear ensures smooth gear changing and quieter operation. Improves the temperature bandwidth and helps to prevent oxidation of the gear oil.

Area of application

Suitable for all manual gearboxes and differentials. Do not use for automatic transmissions or wet clutches.

Application

Add to the oil system. This product is compatible with all commercially available gear oils.

Consumption

50 ml sufficient to treat 2 - 3 litres of oil

Reaction time

Works during operation

Technical data

Physical state: viscous

Colour: brown Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm3

Water resistant

Available sizes	Item no.	PU



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



CTP GmbH Saalfelder Straße 35 h 07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de