

Petrol System Cleaner LPG

Product properties

This high-performance product has especially been developed for liquefied petroleum gas (LPG) powered vehicles. Even smallest particles of contamination and resin deposits in the combustion chambers are lastingly dissolved (Keep Clean Effect). Highly active lubricating components guarantee reliable protection of the valves against wear and tear and corrosion. The product optimises the fuel consumption and emission and extends the life span of the engine and ensures optimal protection against "valve impact". Regular use ensures longterm stability of the fuel.

Area of application

Application to the fuel tank of bivalent vehicles (gas/petrol powered).

Application

Add regularly every 3 to 4 months or every 10,000 km to the fuel system prior to filling up. Optimal results will be achieved when the product "LPG System Clean and Protect" is used in combination.

Consumption

375 ml sufficient for 80 litres fuel. Mix Ratio 1:200

Reaction time

Works during operation.

Technical data

Physical state: liquid

Colour: red

Odour: aromatic

Initial boiling point and boiling range: 110 - 116 °C

Flashpoint: -7,5 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 12 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available sizes	Item no.	PU
375ml	33346	28



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.