

Diesel Anti-Bacteria

Product properties

High Performance Diesel System Care with anti bactericid formula. Diesel Anti Bacteria disinfects the complete diesel system. Destroys bacteria, fungus and algae. It prevents new growth and hinders the blockage of the fuel filter.

Area of application

All diesel engines, in addition to the fuel tank.

Application

Attention: Restricted to professional users!

The Diesel Anti-Bacteria should be added to the fuel tank regularly every 3 to 4 months.

DANGER

Use biocides safely.

Always read the label and product information before use.

Contains: 1 g / 100 g of N, N'-methylen-bis- (5-methyloxazolidine)

Reg-Nr .: N- 36175

Hazard statements

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear suitable gloves. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If skin irritation occurs: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of this material and its container to hazardous or special waste collection point.

Consumption

300 ml sufficient for 60-80 ltr. Diesel, Mixing ratio 1:200

Reaction time

Works during operation.

Technical data

Physical state: liquid Colour: clear/colourless Odour: aromatic

Oudui. aidilialic

Initial boiling point and boiling range: 135 - 145 °C

Flashpoint: 24 °C

Density at 68 °F: 0.87 g/cm³

Available Item no. PU

sizes 300ml 33162 24

Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



CTP GmbH Saalfelder Straße 35 h 07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de