

Oil Anti Smoke

Product properties

Innovative mixture of products which significantly reduces exhaust smoke and soot generation for all 4-stroke-, LPG and diesel powered engines. Ideal for vehicles with high consumption of oil. The product ensures optimal lubrication of all moving parts and reduces the oxidation of the engine oil. Due to this, the engine is noise will be lower, smoke is extremely reduced, the wear decreases and the lifetime of the unit is increased. The high viscosity prevents oil from entering the combustion chamber.

Area of application

For use in all 4-stroke, diesel and LPG powered engines. This product is compatible with all commercially available oils.

Application

Add to oil system. We recommend an oil system cleaning with Oil System Cleaner before using this product. Total Oil volume according to manufacturer specifications must be observed.

Consumption

300 ml sufficient for 5 liter of oil. Mixing ratio: 1:15

Reaction time

while engine is running

Technical data

Physical state: viscous

Colour: brown Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm³

Water resistant

| Available sizes | Item no. | PU |
|-----------------|----------|----|
| | | |



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



CTP GmbH Saalfelder Straße 35 h 07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de