

# Diesel Anti-Bacteria 1:200 (DAB)

# Diesel Anti Bacteria

## **Product properties**

Diesel Anti-Bactericide disinfects the complete diesel system. Destroys bacteria, fungus and algae. It prevents new growth and hinders the blockage of the fuel filter.

#### Area of application

All diesel engines, in addition to the fuel tank.

## **Application**

# ATTENTION: Restricted to professional users!

The Diesel Anti-Bacteria should be added to the fuel tank regularly every 3 to 4 months.

#### **DANGER**

Use biocides safely.

Always read the label and product information before use.

Contains: 1 g / 100 g of N, N'-methylenebis (5-methyloxazolidine)

Reg No.: N- 36118

## **Hazard statements**

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

## **Precautionary statements**

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear suitable gloves. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If skin irritation occurs: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of this material and its container to hazardous or special waste collection point.

#### Consumption

375 ml sufficient for 60-80 ltr. Diesel. Mixing ratio 1:200

## Reaction time

Works during operation.

# **Technical data**

Physical state: liquid Colour: clear/colourless

Odour: aromatic

Initial boiling point and boiling range: 135 - 145 °C

Flashpoint: 24 °C

Density at 68 °F: 0.87 g/cm<sup>3</sup>

Available sizes Item no. PU 375ml P1253 28

375ml P1253 28

Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



CTP GmbH Saalfelder Straße 35 h 07338 Leutenberg Germany

Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22 www.bluechemgroup.com www.ctp.de