

# Automatic Transmission Flush (ATF)

## Automatic Transmission Flush

### Product properties

PRO-TEC Automatic Transmission Flush solves and reliably removes resins, oxidized oil residues, operational deposits and impurities in the transmission oil circuit. The automatic gearbox cleans the entire system. It has a noise-reducing effect and ensures a safe and easy-to-operate gear shift, optimizes the switching behavior and avoids costly repairs.

### Area of application

For all kinds of automatic transmissions

### Application

Add the product to the automatic transmissions oil system before changing the oil. **Caution:** Do not overfill the system. Run the system for approx. 10-15 minutes under frequent load alteration. Afterwards change of the transmission oil accordance to the manufacturer's instructions.

### Consumption

375 ml sufficient for 1 vehicle, Mixing Ratio 1:10

### Reaction time

approx. 10-15 min.

### Technical data

Physical state: liquid

Colour: yellow

Odour: aromatic

Initial boiling point and boiling range: 180 - 220 °C

Flashpoint: 63 °C

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 20 hPa

Density at 68 °F: 0.82 - 0.90 g/cm<sup>3</sup>

Water resistant

Available sizes	Item no.	PU
375ml	P1701	28
1L	P1709	12
5L	P1702	4



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

04.10.2019