

Automatic Transmission Conditioner (ATC)

Automatic Transmission Conditioner

Product properties

Automatic Transmission Conditioner reduces friction, facilitates the shifting process and supports the maintenance of seals and sealing rings. This results in smoother shifting and longer shelf life. The re-deposition of resins and similar contaminants is retarded, the oxidation is slowed, the heat loss is reduced, and optimum lubrication is ensured. This results in improved performance, extended oil change intervals and lower operating and maintenance costs.

Area of application

For all converter and CVT transmissions as well as automatic gearboxes without wet clutch.

Application

Add Automatic Transmission Protection to gear oil. Do not exceed the maximum filling level. If necessary, reduce the oil quantity. Observe the mixing ratio!

Consumption

375 ml sufficient for 1 vehicle, Mixing Ratio 1:10

Reaction time

works during operation

Technical data

Physical state: viscous

Colour: red

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.87 - 0.92 g/cm³

Water resistant

Viscosity / kinematic (at 104 °F): 45,9 mm²/s

| Available sizes | Item no. | PU |
|-----------------|----------|----|
| 375ml | P1801 | 28 |



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.