

# Radiator Flush (RF)

## Radiator Flush

### Product properties

PRO-TEC Radiator Flush removes operational deposits in the entire cooling system. It removes also lime and fur deposits, protects against rust and corrosion, dissolves dangerous radiator sludge and cleans water coolers, boilers and heat exchangers. The product makes valves, thermostats and water pumps free again. The use of PRO-TEC Radiator Flush increase the reliability and lifetime of the engine. Also the heating and cooling performance will be improved.

### Area of application

For use in all cooling water circuits of petrol and diesel engines or industrial equipment

### Application

Prior to each coolant change, admit PRO-TEC Radiator Flush to the used coolant. Run the cooling system or the engine at idle (depending on the size of the system) for approx. 15-40 minutes. After draining rinse with fresh water. Then perform coolant change according to the manufacturer's instructions. We recommend preventive use of PRO-TEC Radiator Conditioner after changing the coolant.

### Consumption

375ml sufficient for 5 - 10 liters of cooling water. Mix Ratio 1:20

### Reaction time

15-40 minutes, depending on the size of the system

### Technical data

Physical state: liquid

Colour: yellow

Odour: odourless

Melting point: < 0 °C

Initial boiling point and boiling range: > 100 °C

Density at 68 °F: 1,07 g/cm<sup>3</sup>

Water soluble

Available sizes	Item no.	PU
375ml	P1501	28
5L	P1502	4



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.