

## Easy Gear (EG)

### Easy Gear

#### Product properties

The highly effective anti-friction barrier seals all the internal surfaces of engines and equipment. Remarkably reduces wear and tear and guarantees optimized lubrication throughout the temperature range. Keeps seals, shaft seals and "o" rings soft and supple. Easy Gear ensures smooth gear changing and quieter operation. Improves the temperature bandwidth and helps to prevent oxidation of the gear oil.

#### Area of application

In all manual gearboxes, secondary and differential transmissions. Do not use in automatic transmissions and gearboxes with wet clutches.

#### Application

Add to the gear oil. Use with every oil change or the used oil (observe the maximale filling quantity, reduce the oil quantity if necessary). The product is miscible with all commercially available oils. Observe the mixing ratio!

#### Consumption

50 ml for 2-3 ltr. gear oil. Mixing Ratio 1:60

#### Reaction time

Works during operation

#### Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm<sup>3</sup>

Water resistant

Available sizes	Item no.	PU
50ml	P2171	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.



Made in Germany

CTP GmbH  
Saalfelder Straße 35 h

07338 Leutenberg  
Germany

Tel.: +49 (0)36734 230-0  
Fax: +49 (0)36734 230-22

www.bluechemgroup.com  
www.ctp.de

04.10.2019