



Revision date: 10.03.2020

Rust Remover 400ml Product code: 301

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rust Remover 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax:+49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, DiplChem.	Telephone:+49 (0)36734 230-19
Internet:	www.bluechemgroup.com	
1.4. Emergency telephone	GBK GmbH: +49-(0)6132-84463 (24/7)	

number:

Further Information

Article Number: 22052

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Kerosene (Mineral Oil), hydrodesulfurised

Danger

Signal word:

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.





Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 2 of 10

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing aerosole.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

alcoholes Corrosion inhibitors.





Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 3 of 10

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification	•	•	
64742-48-9	Hydrocarbons, C10-C13, n-Alkan	es, Isoalkanes, Cyclics, <	2% Aromatics	10 - 20 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066	·	·	
(64742-81-0)	Hydrocarbons, C11-C14, n-alkane	es, isoalkanes, cyclics, ar	omatics (2-25 %)	10 - 20 %
	925-653-7		01-2119458869-15	
	Asp. Tox. 1, Aquatic Chronic 3; H	304 H412 EUH066		
64742-81-0	Kerosene (Mineral Oil), hydrodes	ulfurised		10 - 20 %
	265-184-9		01-2119462828-25	
	Skin Irrit. 2, STOT SE 3, Asp. Tox	. 1, Aquatic Chronic 2; H	315 H336 H304 H411	
64742-53-6	Distillates, hydrotreated light, nap	10 - 20 %		
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304	·		
74-98-6	propane	10 - 20 %		
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Compressed gas; H	220 H280		
75-28-5	isobutane			10 - 20 %
	200-857-2		01-2119485395-27	
	Flam. Gas 1, Compressed gas; H	220 H280		
106-97-8	Butane			2,5 - 10 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Compressed gas; H	220 H280		
111-76-2	2-butoxyethanol, butyl cellosolve,	ethylene glycol monobut	yl ether	1 - 2,5 %
	203-905-0		01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an opthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 4 of 10

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation. Irritation of eyes: Irritant effect possible.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur:

unconsciousness. Intoxication. vomiting. drowsiness. Headache.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Carbon dioxide (CO2). Water fog. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Explosive. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.





Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 5 of 10

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol		Post shift

8.2. Exposure controls

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Provide for good ventilation, when develop aerosols/mist.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Aerosol yellowish characteristic	
Changes in the physical state		
Ignition temperature:		> 200 °C
Density (at 20 °C):		0,705 g/cm³
Water solubility: (at 20 °C)		insoluble
Solvent content:		85,5 %
9.2. Other information		

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.





Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 6 of 10

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No dangerous reactions are known.

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	lo Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13,	n-Alkanes,	lsoalkanes, (Cyclics, < 2% Aromatics		
	oral	LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit		
	inhalation (4 h) gas	LC50	>5 ppm	Rat		
111-76-2	2-butoxyethanol, butyl ce	llosolve, eth	ylene glycol	monobutyl ether		
	oral	LD50 mg/kg	1300	Rat		
	dermal	ATE mg/kg	1100			
	inhalation (4 h) vapour	LC50	>10 mg/l	Guinea pig		
	inhalation aerosol	ATE	1,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Kerosene (Mineral Oil), hydrodesulfurised)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information





Rust Remover 400ml

Revision date: 10.03.2020

Product code: 301

Page 7 of 10

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
64742-48-9	Hydrocarbons, C10-C13,	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 1000 mg/l	0 96 h	Oncorhynchus mykiss			
	Acute algae toxicity	ErC50 1000 mg/l		Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50 1000 mg/l		Daphnia magna (Big water flea)			

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water. Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
75-28-5	isobutane	2,8

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Arrange about the exact waste code with the local waste disposal expert.

Analige about the exact waste code with the local waste disposal e

Do not dispose with household waste.

Contaminated packaging

Dispose of waste according to applicable legislation. Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
	Propane/butane-mixture
14.3. Transport hazard class(es):	2
14.4. Packing group:	-



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Revision date: 10.03.2020	Rust Remover 400ml Product code: 301	Page 8 of 10
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1 L	
Excepted quantity:	EO	
Transport category: Hazard No:	2	
Hazard No: Tunnel restriction code:	- D	
Inland waterways transport (ADN) <u>14.1. UN number:</u>	UN 1950	
	AEROSOLS	
14.2. UN proper shipping name:	Propane/butane-mixture	
<u>14.3. Transport hazard class(es):</u>	2	
14.4. Packing group:	-	
Hazard label:	2.1	
	2	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	E0	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS Propane/butane-mixture	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Marine pollutant:	-	
Special Provisions:	63, 190, 277, 327, 344, 381, 959	
Limited quantity:	1000 mL	
Excepted quantity: EmS:	EO	
Air transport (ICAO-TI/IATA-DGR)	F-D, S-U	
	UN 1950	
<u>14.1. UN number:</u>		
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE Propane/butane-mixture	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	





Rust Remover 400ml					
Revision date: 10.03.2020	Product	code: 301	Page 9 of 1		
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity:	A145 A167 A802 30 kg G Y203 E0				
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		203 75 kg 203 150 kg			
14.5. Environmental hazards					
ENVIRONMENTALLY HAZARDOUS:	no				
14.6. Special precautions for user No information available.					
14.7. Transport in bulk according to Annex No information available.	II of Marpol and the IE	<u>3C Code</u>			
SECTION 15: Regulatory information					
15.1. Safety, health and environmental regu	ulations/legislation spe	ecific for the substance or mixture			
EU regulatory information Restrictions on use (REACH, annex XVII) Entry 28: Hydrocarbons, C10-C13, n- light, naphthenic; isobutane; Butane		yclics, < 2% Aromatics; Distillates, hydrotreated			
2004/42/EC (VOC):	602,6 g/l				
Additional information Contains: > 30 % hydrocarbons, aliphatic.					
National regulatory information					
Water hazard class (D):	2 - obviously hazard	lous to water			
15.2. Chemical safety assessment					
Chemical safety assessments for sub	stances in this mixture	were not carried out.			

This data sheet contains changes from the previous version in section(s): 1,2,3,11,14,15.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.





Rust Remover 400ml

Revision date: 10.03.2020	Product code: 301	Page 10 of 10
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)