

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Triple X Air Intake System Cleaner Petrol

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Cleaning agent for Fuel Systems

**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

**1.4. Emergency telephone number:** GBK GmbH: +49-(0)6132-84463 (24/7)

**Further Information**

Article Number: 1972, 1973

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3  
Aspiration hazard: Asp. Tox. 1  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Dam. 1  
Specific target organ toxicity - single exposure: STOT SE 3  
Specific target organ toxicity - single exposure: STOT SE 3  
Specific target organ toxicity - repeated exposure: STOT RE 2  
Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Regulation (EC) No. 1272/2008**

**Hazard components for labelling**

2-methylpropan-1-ol; iso-butanol  
xylene  
Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates  
isotridecanole, ethoxylised

**Signal word:** Danger

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 2 of 13

**Pictograms:**



**Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H304-H318-H335-H336-H373-H412

**Precautionary statements**

P101-P102-P271-P280-P301+P310-P331-P305+P351+P338-P310-P405-P501

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Surface tension compounds  
Detergents, Dispersants  
Synthetic agent combinations  
Anti wear agents not classified

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 3 of 13

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	GHS Classification	
78-83-1	2-methylpropan-1-ol; iso-butanol	30 - < 35 %
	201-148-0 01-2119484609-23	
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336	
1330-20-7	xylene	25 - < 30 %
	215-535-7 01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates	20 - < 25 %
	919-857-5 01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066	
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates	5 - < 10 %
	920-134-1 01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066	
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)	5 - < 10 %
	Aquatic Chronic 2; H411	
64742-95-6	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom. Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline),hydrotreated heavy	5 - < 10 %
	918-668-5 01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066	
69011-36-5	isotridecanole, ethoxylised	1 - < 5 %
	931-138-8	
	Acute Tox. 4, Eye Dam. 1; H302 H318	

Full text of H and EUH statements: see section 16.

**Specific concentration limits and M-factors**

CAS No	EC No	Chemical name	Quantity
		Specific concentration limits and M-factors	
69011-36-5	931-138-8	isotridecanole, ethoxylised	1 - < 5 %
		Eye Dam. 1; H318: >= 10,1 - 100 Eye Irrit. 2; H319: >= 1 - < 10,1	

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Move victim to fresh air. Put victim at rest and keep warm.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 4 of 13

Rub greasy ointment into the skin.

**After contact with eyes**

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

**After ingestion**

Let water be drunken in little sips (dilution effect). Consult physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

**6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

**6.4. Reference to other sections**

No data

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 5 of 13

**Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.  
Avoid contact with skin and eyes.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

**Further information on storage conditions**

Packaging materials: metal.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
78-83-1	Isobutyl alcohol	50	150		TWA (8 h)	
		75	225		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

**8.2. Exposure controls**

**Protective and hygiene measures**

When using do not eat, drink or smoke.  
Wash hands before breaks and after work.

**Eye/face protection**

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

**Hand protection**

Tested protective gloves are to be worn: Butyl rubber. (EN ISO 374)

**Skin protection**

Wear suitable solvent-proof protective clothing according to EN 465.

**Respiratory protection**

In case of accumulation of fumes/aerosols, provide adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: liquid  
Colour: transparent  
Odour: aromatic

**Changes in the physical state**

Initial boiling point and boiling range: 110 - 120 °C  
Flash point: 24 °C  
Lower explosion limits: 0,6 vol. %

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 6 of 13

Upper explosion limits:	12 vol. %
Ignition temperature:	> 200 °C
Vapour pressure: (at 20 °C)	20 hPa
Density (at 20 °C):	0.82 - 0.84 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble

**Solubility in other solvents**

Organic solvents

**9.2. Other information**

No data

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No decomposition when used as intended.

**10.3. Possibility of hazardous reactions**

No dangerous reactions are known.

**10.4. Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

**10.5. Incompatible materials**

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

**10.6. Hazardous decomposition products**

Carbon monoxide (CO).

Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 7 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 24 mg/l	Rat		
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 3200 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat		
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat		
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
64742-95-6	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom. Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline),hydrotreated heavy				
	oral	LD50 >3000 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rat		
69011-36-5	isotridecanole, ethoxylised				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 8 of 13

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (2-methylpropan-1-ol; iso-butanol; xylene)

May cause drowsiness or dizziness. (2-methylpropan-1-ol; iso-butanol; Hydrocarbons, C9-C 11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**

**12.1. Toxicity**



**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 1430 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 1250 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 1439 mg/l	48 h	Daphnia magna		
1330-20-7	xylene					
	Acute fish toxicity	LC50 26,7 mg/l	96 h	Pimephales promelas		
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna		
64742-47-8	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna		
	Poly[oxy(1,2-butanediyl)], .alpha.-(3-aminopropyl)-.gamma.-hydroxy-, C11-14-isoalkyl ethers, C13-rich (Polyetheramines)					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 10-100 mg/l	72 h	Algae		
64742-95-6	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom. Low boiling point hydrogen treated naphtha, Naphtha (petroleum, gasoline),hydrotreated heavy					
	Acute fish toxicity	LC50 1 - 10 mg/l	96 h	Daphnia magna		
69011-36-5	isotridecanole, ethoxylised					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Fish		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna		

**12.2. Persistence and degradability**

No information available.

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 10 of 13

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
69011-36-5	isotridecanole, ethoxylised			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28	
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28	

**12.3. Bioaccumulative potential**

Swims on the water.

Low potential of bio-accumulation.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

No information available.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

**Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 11 of 13

Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 274 601  
Limited quantity: 5 L  
Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: -  
Special Provisions: 223, 274, 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 12 of 13

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

**Additional information**

Contains:

> 30 % aliphatic hydrocarbons

15 - 30 % aromatic hydrocarbons

< 5 % nonionic tensides

**National regulatory information**

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,8,11,14,15.

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Triple X Air Intake System Cleaner Petrol**

Revision date: 14.01.2021

Product code: 1388

Page 13 of 13

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*