

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Common-Rail Diesel System Clean & Protect

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent for Diesel Systems

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number: GBK GmbH: +49-(0)6132-84463 (24/7)**Further Information**

Article Number: 33098, 33099, 33097, 33090, 33094, 33096, 33092

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

xylene

toluene

isotridecanole, ethoxylised

Signal word: Danger**Pictograms:**

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 2 of 11

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour/aerosole.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P314	Get medical advice/attention if you feel unwell.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word:

Danger

Pictograms:



Hazard statements

H304-H361d-H373

Precautionary statements

P101-P102-P260-P280-P301+P310-P331-P405-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Additives
Organic solvents
Lubricants

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			65 - < 80 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
1330-20-7	xylene			10 - < 15 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts			5 - < 10 %
	274-263-7		01-2119492616-28	
108-88-3	toluene			1 - < 5 %
	203-625-9		01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
69011-36-5	isotridecanole, ethoxylised			1 - < 5 %
	931-138-8			
	Acute Tox. 4, Eye Dam. 1; H302 H318			

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity
	Specific concentration limits and M-factors		
69011-36-5	931-138-8	isotridecanole, ethoxylised	1 - < 5 %
	Eye Dam. 1; H318: >= 10,1 - 100 Eye Irrit. 2; H319: >= 1 - < 10,1		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .

Subsequently wash off with: Water and soap.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

**Common-Rail Diesel System Clean & Protect**

Revision date: 22.10.2020

Product code: 2392

Page 4 of 11

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Extinguishing powder. Sand. Carbon dioxide (CO₂). alcohol resistant foam.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Beat down gas/vapours/mist with water spray.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear a self-contained breathing apparatus and chemical resistant suit.

Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 5 of 11

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Protective and hygiene measures

- Take off immediately all contaminated clothing
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin and eyes.
- Keep away from food, drink and animal feeding stuffs.
- When using do not eat, drink or smoke.
- Wash hands before breaks and after work.

Eye/face protection

- Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

- Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

- Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

- In case of accumulation of fumes/aerosols, provide adequate ventilation.
- In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	brown
Odour:	aromatic

Changes in the physical state

Initial boiling point and boiling range:	200 - 210 °C
Flash point:	45 °C
Lower explosion limits:	> 0,6 vol. %
Upper explosion limits:	> 7,0 vol. %
Ignition temperature:	> 200 °C
Vapour pressure: (at 20 °C)	> 8 hPa
Density (at 20 °C):	0.824 - 0.9 g/cm ³



Safety Data Sheet

bluechem 
GROUP

according to Regulation (EC) No 1907/2006

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 6 of 11

Water solubility:
(at 20 °C) insoluble

Solubility in other solvents
Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.
No decomposition when used as intended.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) gas	LC50 >5 ppm	Rat		
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 3200 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
108-88-3	toluene				
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat	GESTIS	
69011-36-5	isotridecanole, ethoxylised				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna (Big water flea)		
1330-20-7	xylene					
	Acute fish toxicity	LC50 26,7 mg/l	96 h	Pimephales promelas		
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
108-88-3	toluene					
	Acute fish toxicity	LC50 13 mg/l	96 h	Carassius auratus	IUCLID	
	Acute algae toxicity	ErC50 12,5 mg/l	72 h		GESTIS	
69011-36-5	isotridecanole, ethoxylised					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Fish		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No information available.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
69011-36-5	isotridecanole, ethoxylised				
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28		
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28		

12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 9 of 11

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Container must be completely emptied.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (xylene, toluene)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (xylene, toluene)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 10 of 11

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
 (xylene, toluene)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: -
 Special Provisions: 223, 274, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
 (xylene, toluene)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

Entry 48: toluene

Additional information



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Common-Rail Diesel System Clean & Protect

Revision date: 22.10.2020

Product code: 2392

Page 11 of 11

Contains: (Regulation (EC) No. 648/2004 (Detergents regulation))

> 30 % hydrocarbons, aliphatic.

5 - 15 % hydrocarbons, aromatic.

< 5 % nonionic tensides

National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,11,14,15.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)