

# Diesel Anti-Bacteria 1:1000 (DAB1000)

Diesel Anti Bacteria 1:1000

## **Product properties**

Diesel Anti-Bactericide disinfects the complete diesel system. Destroys bacteria, fungus and algae. It prevents new growth and hinders the blockage of the fuel filter.

#### Area of application

All diesel engines, adding to the fuel tank.

#### Application

#### **ATTENTION: Restricted to professional users!**

Fill directly into the diesel tank. Observe mixing ratio. Add the product (regularly every 3 to 4 months) at a ratio of 1:1000 (0,1%) to the diesel system before filling up.

### DANGER

Use biocides safely. Always read the label and product information before use. Contains: 2,9 g / 100 g of N, N'-methylen-bis- (5-methyloxazolidine) Reg-Nr .: N- 36122

#### Hazard statements

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear suitable gloves. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Wash with plenty of water. Store locked up. Dispose of this material and its container to hazardous or special waste collection point.

#### Consumption

1 ltr. for 1000 ltr. diesel. Mix Ratio 1:1000

#### **Reaction time**

while engine is running

#### **Technical data**

Physical state: liquid Colour: clear/colourless Odour: aromatic Initial boiling point and boiling range: 135 - 145 °C Flashpoint: 24 °C Density at 68 °F: 0.87 g/cm<sup>3</sup>

Available sizes	Item no.	PU
1L	P1239	12
5L	P1232	4



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.

07338 Leutenberg Germany Tel.: +49 (0)36734 230-0 Fax: +49 (0)36734 230-22

8.02.202