

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Autoprofi Easy Gear

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Oil Performance Improver

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 43238

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate

Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alcyl derivs. para-,calcium salts

Signal word: Warning

Pictograms:



Hazard statements

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing vapour/aerosole.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 2 of 8

P333+P313

If skin irritation or rash occurs: Get medical advice/attention.

P501

Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word:

Warning

Pictograms:



Hazard statements

H317-H412

Precautionary statements

P101-P102-P261-P280-P333+P313

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Inhibitors

Preventing agent

Anti wear agents not classified

Anti Friction Components

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-56-9	Basic mineral oils			10 - < 15 %
	265-159-2		01-2119480132-48	
	Asp. Tox. 1; H304			
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate			5 - < 10 %
	276-159-7		01-2120770937-38	
	Flam. Liq. 3, Skin Sens. 1, Aquatic Chronic 2; H226 H317 H411			
	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alcyl derivs. para-,calcium salts			1 - < 5 %
	947-519-7		01-2120765489-36	
	Skin Sens. 1B; H317			
84605-29-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts			< 1 %
	283-392-8		01-2119493626-26	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411			
121158-58-5	p-Dodecylphenol			< 1 %
	310-154-3		01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 3 of 8

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-56-9	265-159-2	Basic mineral oils	10 - < 15 %
		inhalation: LC50 = >5 mg/l (dusts or mists)	
71888-91-0	276-159-7	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate	5 - < 10 %
		oral: LD50 = >2000 mg/kg	
84605-29-8	283-392-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	< 1 %
		dermal: LD50 = >3200 mg/kg; oral: LD50 = >2000 mg/kg Skin Irrit. 2; H315: >= 6,25 - 100 Eye Dam. 1; H318: >= 12,5 - 100 Eye Irrit. 2; H319: >= 10 - < 12,5	
121158-58-5	310-154-3	p-Dodecylphenol	< 1 %
		M akut; H400: M=10 M chron.; H410: M=10	

SECTION 4: First aid measures

4.1. Description of first aid measures

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .
Subsequently wash off with: Water and soap.
Seek medical attention if problems persist.

After contact with eyes

Remove contact lenses.
Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

After ingestion

Rinse mouth thoroughly with water.
Do NOT induce vomiting.
Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Sand.
Carbon dioxide (CO2).
Water spray.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.
In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 4 of 8

Additional information

- Cool endangered container in case of fire.
- Beat down gas/vapours/mist with water spray.
- Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear a self-contained breathing apparatus and chemical resistant suit.
- High skid risk because of leaking or spilled product.

6.2. Environmental precautions

- Do not empty into drains or the aquatic environment.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

- Prevent spreading of spillages (e.g. by oil barrier).
- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

- No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- The substance should only be handled in closed apparatus or systems.
- Avoid contact with skin and eyes.
- Avoid oil mist

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place.
- Do not store at temperatures over: 50 °C

Hints on joint storage

- Should be stored separately from oxidizing agents.

7.3. Specific end use(s)

- No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

- Take off immediately all contaminated clothing
- Avoid contact with skin and eyes.
- Keep away from food, drink and animal feeding stuffs.
- When using do not eat, drink or smoke.
- Wash hands before breaks and after work.

Eye/face protection

- Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

- Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

- Wear suitable protective clothing.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 5 of 8

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: viscous

Colour: brown

Odour: mild

Changes in the physical state

Flash point: > 100 °C

Density (at 20 °C): 0.89 - 0.92 g/cm³

Water solubility: insoluble
(at 20 °C)

Solubility in other solvents

Organic solvents

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

No decomposition when used as intended.

Keep at temperature not exceeding 50 °C.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 6 of 8

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Basic mineral oils				
	inhalation (4 h) aerosol	LC50 >5 mg/l	Rat		
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate				
	oral	LD50 >2000 mg/kg	Rat		
84605-29-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >3200 mg/kg	Rabbit		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate; Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alcyl derivs. para-,calcium salts)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Other observations

No information available.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
71888-91-0	Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate					
	Acute fish toxicity	LC50 2,55 mg/l	96 h	Brachydanio rerio		
	Acute crustacea toxicity	EL50 4,90 mg/l	48 h	Daphnia magna		
84605-29-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Fish		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

12.3. Bioaccumulative potential

No information available.

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 7 of 8

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Container must be completely emptied.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

according to Regulation (EC) No 1907/2006

Autoprofi Easy Gear

Revision date: 01.03.2021

Product code: 1565

Page 8 of 8

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 30

Additional information

Contains:

< 5 % Phosphate

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,11,12.

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)