



according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Nano Glass Sealant Component 2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

hydrophobing- and oleophobing agent surface-modifier

1.3. Details of the supplier of the safety data sheet

Company name: CTP GmbH

Street: Saalfelder Strasse 35h
Place: D-07338 Leutenberg

Telephone: +49 (0)36734 230-0 Telefax: +49 (0)36734 230-22

e-mail: msds@bluechemgroup.com

Contact person: Jens Moeller, Dipl.-Chem. Telephone: +49 (0)36734 230-19

Internet: www.bluechemgroup.com

1.4. Emergency telephone GBK GmbH: +49-(0)6132-84463 (24/7)

number:

Further Information

Article Number: 21151, 21187, 21159

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 2 of 8

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





Hazard statements

H336

Precautionary statements

P101-P102-P233-P271-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No Index No REACH No				
	GHS Classification				
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			80 - < 85 %	
	00-661-7 01-2119457558-25				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

	-p					
CAS No	EC No	Chemical name	Quantity			
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE				
67-63-0	200-661-7	200-661-7 propan-2-ol; isopropyl alcohol; isopropanol				
	inhalation: LC50 = 47,5 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5280 mg/kg					

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Following inhalation: Move victim to fresh air. Consult physician.

In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Seek medical attention if problems persist.

After contact with eyes

If product gets into the eye, keep e4yelid open and rinse immediately with large quantities of water, for at least





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 3 of 8

5 minutes. Subsequently consult an opthalmologist.

After ingestion

Rinse mouth thoroughly with water.

Let water be drunken in little sips (dilution effect).

Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

After ingestion of absorption substances:

Give activated carbon, in order to reduce the resorption in the gastro-enteric tract.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog.

alcohol resistant foam.

Carbon dioxide (CO2).

Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Cool endangered container in case of fire.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Provide adequate ventilation.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed containers for disposal.

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 4 of 8

Keep away from moisture.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Propan-2-ol	200			TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L		End of shift at end of workweek

8.2. Exposure controls

Protective and hygiene measures

Provide adequate ventilation.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

When using do not eat, drink or smoke.

Protect skin by using skin protective cream.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Suitable material: Butyl rubber. FKM (Fluoroelastomer (Viton)).

Material thickness: 0.4 - 0.5 mm penetration time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist generation.

Wear suitable breathing apparatus (filter typ ABEK).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: colourless cloudy
Odour: product-specific

Test method

pH-Value (at 20 °C): 1,8 (1000 g/l)

Changes in the physical state

Flash point: 14 °C DIN 51755





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 5 of 8

Lower explosion limits: 2 vol. % Upper explosion limits: 12 vol. %

 Density (at 20 °C):
 0,89 g/cm³
 DIN 51757

 Viscosity / dynamic:
 3,7 mPa·s
 DIN 53015

(at 20 °C)

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

Reacts violently with: Oxidizing agents, strong.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

None

thermal decomposition: standard pressure decomposition distillable

Reacts violently with: Oxidizing agents, strong.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Vapours may cause drowsiness and dizziness.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	oral	LD50 mg/kg	5280	Rat		
	dermal	LD50 mg/kg	12800	Rabbit		
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 6 of 8

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Other observations

No information available.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Algae		
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna		

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Carry out a burning of harzardous waste according to official regulations.

For this product, the waste identity number according to the European waste catalogue cannot be defined

because the designated use by the consumer allows the classification first.

Arrange about the exact waste code with the local waste disposal expert.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3





according to Regulation (EC) No 1907/2006

Nano Glass Sealant Component 2

Revision date: 05.07.2021 Product code: 1596 Page 7 of 8



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1219

14.2. UN proper shipping name: ISOPROPYL ALCOHOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A180
Limited quantity Passenger: 1 L





according to Regulation (EC) No 1907/2006

Revision date: 05.07.2021 Product code: 1596 Page 8 of 8

Passenger LQ: Y341 Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)