

**Bio Multi Spray 500ml**

Revision date: 16.09.2021

Product code: 548

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Bio Multi Spray 500ml

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and additive.

**1.3. Details of the supplier of the safety data sheet**

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

**1.4. Emergency telephone number:** GBK GmbH: +49-(0)6132-84463 (24/7)**Further Information**

Article Number: 37022

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Distillates (petroleum, gasoline), hydrotreated light

**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Bio Multi Spray 500ml**

Revision date: 16.09.2021

Product code: 548

Page 2 of 10

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing aerosole.  
P271 Use only outdoors or in a well-ventilated area.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of this material and its container to hazardous or special waste collection point.

**Special labelling of certain mixtures**

- EUH066 Repeated exposure may cause skin dryness or cracking.

**Labelling of packages where the contents do not exceed 125 ml**

Signal word: Danger

Pictograms:

**Hazard statements**

H222-H229-H336

**Precautionary statements**

P101-P102-P210-P211-P251-P261-P271-P304+P340-P312-P410+P412-P501

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Solvent mixture

Aerosol propellant:

Propane/butane-mixture

## Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 3 of 10

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light			35 - < 40 %
	265-149-8			
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066			
106-97-8	Butane			20 - < 25 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; H220 H280			
74-98-6	propane			15 - < 20 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H220 H280			
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether			1 - < 5 %
	203-905-0		01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-47-8	265-149-8	Distillates (petroleum, gasoline), hydrotreated light	35 - < 40 %
		inhalation: LC50 = 13100 mg/l (vapours); dermal: LD50 = 3400 mg/kg; oral: LD50 = >15000 mg/kg	
111-76-2	203-905-0	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	1 - < 5 %
		inhalation: LC50 = >10 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 1300 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down.  
Change contaminated clothing.

#### After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.  
In case of skin irritation, seek medical treatment.

#### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Consult physician.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.



**Bio Multi Spray 500ml**

Revision date: 16.09.2021

Product code: 548

Page 4 of 10

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Extinguishing powder.  
Carbon dioxide (CO<sub>2</sub>).  
Water fog.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Swims on the water. Vapours are heavier than air and will spread at floor level.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Cool endangered container in case of fire.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes.  
Do not breathe gas/fumes/vapour/spray.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

**6.4. Reference to other sections**

Explosive. Vapours may form explosive mixtures with air.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Keep only in the original container in a cool, well-ventilated place. Have to care for a good Ventilation at workplace.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.  
Vapours may form explosive mixtures with air.  
Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C  
Heating causes rise in pressure with risk of bursting.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

## Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 5 of 10

### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
111-76-2	2-Butoxyethanol (EGBE)	20	98		TWA (8 h)	
		50	246		STEL (15 min)	
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	

### Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	BAA	200 mg/g	Creatinine	End of shift

### 8.2. Exposure controls

#### Protective and hygiene measures

- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.
- Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

#### Eye/face protection

- Wear tightly sealed safety glasses against possible splashes into the eyes.

#### Hand protection

- Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

#### Respiratory protection

- Have to care for a good Ventilation at workplace.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

#### Changes in the physical state

Boiling point or initial boiling point and boiling range:	< 0 °C
Upper explosion limits:	-
Auto-ignition temperature:	> 200 °C
Density (at 20 °C):	0,699 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	sparingly soluble.

### 9.2. Other information

No data

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No decomposition when used as intended.

## Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 6 of 10

### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4. Conditions to avoid

Do not store at temperatures over: 50 °C  
Keep away from heat.

### 10.5. Incompatible materials

strong acids  
Alkali (lye)

### 10.6. Hazardous decomposition products

No decomposition when used as intended.  
No dangerous reactions are known.  
Carbon monoxide.  
Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light				
	oral	LD50 >15000 mg/kg	Rat		
	dermal	LD50 3400 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 13100 mg/l	Rat		
111-76-2	2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether				
	oral	LD50 1300 mg/kg	Rat		
	dermal	ATE 1100 mg/kg			
	inhalation (4 h) vapour	LC50 >10 mg/l	Guinea pig		
	inhalation aerosol	ATE 1,5 mg/l			

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Distillates (petroleum, gasoline), hydrotreated light)

#### STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Practical experience



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 7 of 10

#### Other observations

No information available.

### SECTION 12: Ecological information

#### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light					
	Acute fish toxicity	LC50	10 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	10 mg/l	48 h	Daphnia magna	

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

No information available.

#### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not dispose with household waste.

##### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### Contaminated packaging

Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number:

UN 1950

## Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 8 of 10

**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Hazard No: -  
Tunnel restriction code: D

### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
Propane/butane-mixture  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Marine pollutant: P  
Special Provisions: 63, 190, 277, 327, 344, 381, 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
Propane/butane-mixture



## Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 9 of 10

### 14.3. Transport hazard class(es):

2.1

### 14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y203

Excepted quantity:

E0

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

Distillates (petroleum, gasoline), hydrotreated light

### 14.6. Special precautions for user

No information available.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29

2004/42/EC (VOC):

599,7 g/l

#### Additional information

Contains:

> 30 % aliphatic hydrocarbons

#### National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Butane

propane

2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1,2,8,11,12,14,15.



## Safety Data Sheet

**bluechem**   
**GROUP**

according to Regulation (EC) No 1907/2006

### Bio Multi Spray 500ml

Revision date: 16.09.2021

Product code: 548

Page 10 of 10

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*