

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Autoprofi Guard Fill Petrol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cleaning agent for Fuel Systems

### 1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

### 1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

#### Further Information

Article Number: 43239

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

mixture of hydrocarbons (aromatic) C9-C10

Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Signal word: Danger

Pictograms:



according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 2 of 10

#### Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing Gas/Vapour/aerosole.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.


#### Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H304-H335-H336

#### Precautionary statements

P101-P102-P261-P301+P310-P331-P405-P501

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Surface tension compounds  
Detergents, Dispersants  
Synthetic agent combinations  
Anti wear agents not classified

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 3 of 10

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-95-6	mixture of hydrocarbons (aromatic) C9-C10			70 - < 75 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
64742-94-5	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified			10 - < 15 %
	265-198-5		01-2119463583-34	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411 EUH066			
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics			5 - < 10 %
	926-141-6		01-2119456620-43	
	Asp. Tox. 1; H304 EUH066			
69011-36-5	isotridecanole, ethoxylised			1 - < 5 %
	931-138-8			
	Acute Tox. 4, Eye Dam. 1; H302 H318			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-95-6	918-668-5	mixture of hydrocarbons (aromatic) C9-C10	70 - < 75 %
		dermal: LD50 = >3160 mg/kg; oral: LD50 = >3000 mg/kg	
64742-94-5	265-198-5	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified	10 - < 15 %
		inhalation: LC50 = >590 mg/l (vapours); dermal: LD50 = >2 mg/kg; oral: LD50 = 5 mg/kg	
64742-47-8	926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	5 - < 10 %
		inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
69011-36-5	931-138-8	isotridecanole, ethoxylised	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg Eye Dam. 1; H318: >= 10,1 - 100 Eye Irrit. 2; H319: >= 1 - < 10,1	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Move victim to fresh air. Put victim at rest and keep warm.

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

##### After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of water and soap.

Rub greasy ointment into the skin.

##### After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Consult physician.

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 4 of 10

#### After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Warning about danger of aspiration.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO<sub>2</sub>).

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition - No smoking.

#### **6.2. Environmental precautions**

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

#### **6.4. Reference to other sections**

No data

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 5 of 10

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

##### Further information on storage conditions

Packaging materials: metal.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

##### Protective and hygiene measures

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

##### Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

##### Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN ISO 374)

##### Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

##### Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light yellow
Odour:	aromatic

##### Changes in the physical state

Flash point:	50 °C
Auto-ignition temperature:	> 200 °C
Density (at 20 °C):	0.88 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	insoluble

##### Solubility in other solvents

Organic solvents

#### 9.2. Other information

No data

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No decomposition when used as intended.

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 6 of 10

#### 10.3. Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

#### 10.5. Incompatible materials

Oxidizing agents, acid, concentrated. Alkalis (alkalis), concentrated.

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO).

Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-95-6	mixture of hydrocarbons (aromatic) C9-C10				
	oral	LD50 >3000 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rat		
64742-94-5	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified				
	oral	LD50 5 mg/kg	Rat		
	dermal	LD50 >2 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >590 mg/l	Rat		
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 5000 mg/l	Rat		
69011-36-5	isotridecanole, ethoxylised				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

##### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

May cause respiratory irritation. (mixture of hydrocarbons (aromatic) C9-C10 )

May cause drowsiness or dizziness. (mixture of hydrocarbons (aromatic) C9-C10 )

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 7 of 10

#### STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Practical experience

#### Other observations

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-95-6	mixture of hydrocarbons (aromatic) C9-C10					
	Acute fish toxicity	LC50 1 - 10 mg/l	96 h	Daphnia magna		
64742-94-5	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified					
	Acute fish toxicity	LC50 2-5 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 1-3 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 3-10 mg/l	48 h	Daphnia magna		
69011-36-5	isotridecanole, ethoxylised					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Fish		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna		

### 12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
69011-36-5	isotridecanole, ethoxylised			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28	
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28	

### 12.3. Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	6 - 8

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

No information available.

### 12.6. Other adverse effects

No information available.

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 8 of 10

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.


#### Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.


Do not pierce, cut up or weld unclean container. (Explosion hazard.)

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. mixture of hydrocarbons (aromatic) C9-C10
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
	
Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. mixture of hydrocarbons (aromatic) C9-C10
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
	
Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1993
-------------------------	---------



according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 9 of 10

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
mixture of hydrocarbons (aromatic) C9-C10

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Marine pollutant: P

Special Provisions: 223, 274, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.  
mixture of hydrocarbons (aromatic) C9-C10

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 10 L

Passenger LQ: Y344

Excepted quantity: E1

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: mixture of hydrocarbons (aromatic) C9-C10

#### 14.6. Special precautions for user

No information available.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

##### Additional information

according to Regulation (EC) No 1907/2006

### Autoprofi Guard Fill Petrol

Revision date: 30.04.2021

Product code: 2410

Page 10 of 10

Contains:

> 30 % hydrocarbons, aromatic.

#### National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*